

VJ1808A101KBHAT4X

VJ1808A101KBHAT4X Information



For Reference Only

Part Number VJ1808A101KBHAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 100PF 3KV NP0 1808

Package 1808 (4520 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1808A101KBHAT4X Specifications

Manufacturer Part Number VJ1808A101KBHAT4X Manufacturer Vishay Vitramon Category Capacitors Package 1808 (4520 Metric) Series VJ OMD Capacitance 100pF Tolerance ±10% Voltage - Rated 3000V (3kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)		
Category Capacitors Package 1808 (4520 Metric) Series VJ OMD Capacitance 100pF Tolerance ±10% Voltage - Rated 3000V (3kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Manufacturer Part Number	VJ1808A101KBHAT4X
Package 1808 (4520 Metric) Series VJ OMD Capacitance 100pF Tolerance ±10% Voltage - Rated 3000V (3kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Manufacturer	Vishay Vitramon
Package 1808 (4520 Metric) Series VJ OMD Capacitance 100pF Tolerance ±10% Voltage - Rated 3000V (3kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Category	Capacitors
Series VJ OMD Capacitance 100pF Tolerance ±10% Voltage - Rated 3000V (3kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)		Ceramic Capacitors
Capacitance 100pF Tolerance ±10% Voltage - Rated 3000V (3kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Package	1808 (4520 Metric)
Tolerance ±10% Voltage - Rated 3000V (3kV) Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Series	VJ OMD
Voltage - Rated3000V (3kV)Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.186" L x 0.080" W (4.72mm x 2.03mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)	Capacitance	100pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) Thickness (Max) 0.086" (2.18mm)	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) Thickness (Max) 0.086" (2.18mm)	Voltage - Rated	3000V (3kV)
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Temperature Coefficient	C0G, NP0
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Applications	Boardflex Sensitive
Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Failure Rate	-
Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) - 0.086" (2.18mm)	Package / Case	1808 (4520 Metric)
Thickness (Max) 0.086" (2.18mm)	Size / Dimension	0.186" L x 0.080" W (4.72mm x 2.03mm)
	Height - Seated (Max)	-
1 10	Thickness (Max)	0.086" (2.18mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

VJ1808A101KBHAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1808A101KBHAT4X Payment Methods





















VJ1808A101KBHAT4X Shipping Methods













If you have any question about VJ1808A101KBHAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com