

VJ1808A360KBRAT4X

VJ1808A360KBRAT4X Information



For Reference Only

Part Number VJ1808A360KBRAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 36PF 1.5KV NP0 1808

Package 1808 (4520 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1808A360KBRAT4X Specifications

Manufacturer Part Number VJ1808A360KBRAT4X Manufacturer Vishay Vitramon Category Capacitors Package 1808 (4520 Metric) Series VJ OMD Capacitance 36pF Tolerance ±10% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package 1808 (4520 Metric) Series VJ OMD Capacitance 36pF Tolerance ±10% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Manufacturer Part Number	VJ1808A360KBRAT4X
Package 1808 (4520 Metric) Series VJ OMD Capacitance 36pF Tolerance ±10% Voltage - Rated 1500V (1.5kV) Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Manufacturer	Vishay Vitramon
Package 1808 (4520 Metric) Series VJ OMD Capacitance 36pF Tolerance ±10% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Category	Capacitors
Series VJ OMD Capacitance 36pF Tolerance ±10% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 36pF Tolerance ±10% Voltage - Rated 1500V (1.5kV) Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Package	1808 (4520 Metric)
Tolerance ±10% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Series	VJ OMD
Voltage - Rated1500V (1.5kV)Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.186" L x 0.080" W (4.72mm x 2.03mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-Lead Style-	Capacitance	36pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.186" L x 0.080" W (4.72mm x 2.03mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-Lead Style-	Voltage - Rated	1500V (1.5kV)
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 1808 (4520 Metric) Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.186" L x 0.080" W (4.72mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1808 (4520 Metric)
Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Size / Dimension	0.186" L x 0.080" W (4.72mm x 2.03mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.086" (2.18mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

VJ1808A360KBRAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1808A360KBRAT4X Payment Methods



















VJ1808A360KBRAT4X Shipping Methods













If you have any question about VJ1808A360KBRAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com