

VJ1808Y392JBGAT4X

VJ1808Y392JBGAT4X Information



For Reference Only

Part Number VJ1808Y392JBGAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 3900PF 1KV X7R 1808

Package 1808 (4520 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1808Y392JBGAT4X Specifications

| Manufacturer Part Number Manufacturer Vishay Vitramon Category Capacitors Ceramic Capacitors Package 1808 (4520 Metric) Series VJ OMD Capacitance 3900pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) 1808 (4520 Metric) | | |
|---|--------------------------|---------------------------------------|
| Category Capacitors Package 1808 (4520 Metric) Series VJ OMD Capacitance 3900pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Manufacturer Part Number | VJ1808Y392JBGAT4X |
| Ceramic Capacitors Package 1808 (4520 Metric) Series VJ OMD Capacitance 3900pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Manufacturer | Vishay Vitramon |
| Package 1808 (4520 Metric) Series VJ OMD Capacitance 3900pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Category | Capacitors |
| Series VJ OMD Capacitance 3900pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | | Ceramic Capacitors |
| Capacitance 3900pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Package | 1808 (4520 Metric) |
| Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Series | VJ OMD |
| Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Capacitance | 3900pF |
| Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Tolerance | $\pm 5\%$ |
| Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Voltage - Rated | 1000V (1kV) |
| Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Temperature Coefficient | X7R |
| Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Operating Temperature | -55°C ~ 125°C |
| Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Features | Soft Termination, High Voltage |
| Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Ratings | - |
| Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) | Applications | Boardflex Sensitive |
| Package / Case 1808 (4520 Metric) | Failure Rate | - |
| - | Mounting Type | Surface Mount, MLCC |
| Size / Dimension 0.186" I. v. 0.080" W. (4.72mm v. 2.03mm) | Package / Case | 1808 (4520 Metric) |
| 5.150 E x 0.000 W (4.7211111 x 2.0311111) | Size / Dimension | 0.186" L x 0.080" W (4.72mm x 2.03mm) |
| Height - Seated (Max) - | Height - Seated (Max) | - |
| Thickness (Max) 0.086" (2.18mm) | Thickness (Max) | 0.086" (2.18mm) |
| Lead Spacing - | Lead Spacing | - |
| Lead Style - | Lead Style | - |
| Report errors? | | Report errors? |

VJ1808Y392JBGAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1808Y392JBGAT4X Payment Methods





















VJ1808Y392JBGAT4X Shipping Methods













If you have any question about VJ1808Y392JBGAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com