

# VJ1812A120JNRAR

### VJ1812A120JNRAR Information

Heisener.com

Part Number VJ1812A120JNRAR
Manufacturer Vishay Vitramon

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 12PF 1.5KV C0G/NP0 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **VJ1812A120JNRAR Specifications**

Manufacturer Part Number         VJ1812A120JNRAR           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         1812 (4532 Metric)           Series         VJ           Capacitance         12pF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         1812 (4532 Metric)           Series         VJ           Capacitance         12pF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	VJ1812A120JNRAR
Package         1812 (4532 Metric)           Series         VJ           Capacitance         12pF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Vishay Vitramon
Package         1812 (4532 Metric)           Series         VJ           Capacitance         12pF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         VJ           Capacitance         12pF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance       12pF         Tolerance       ±5%         Voltage - Rated       1500V (1.5kV)         Temperature Coefficient       C0G, NPO         Operating Temperature       -55°C ~ 125°C         Features       Non-Magnetic         Ratings       -         Applications       General Purpose         Failure Rate       -         Mounting Type       Surface Mount, MLCC         Package / Case       1812 (4532 Metric)         Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.086" (2.18mm)         Lead Spacing       -         Lead Style       -	Package	1812 (4532 Metric)
Tolerance ±5%  Voltage - Rated 1500V (1.5kV)  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features Non-Magnetic  Ratings -  Applications General Purpose  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) 0.086" (2.18mm)  Lead Spacing -  Lead Style -	Series	VJ
Voltage - Rated  Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  Non-Magnetic  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  1812 (4532 Metric)  Size / Dimension  0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max)  - Thickness (Max)  0.086" (2.18mm)  Lead Spacing  - Lead Style	Capacitance	12pF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  Non-Magnetic  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  1812 (4532 Metric)  Size / Dimension  0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max)  Thickness (Max)  Lead Spacing  - Lead Style  -  COG, NP0  -55°C ~ 125°C  Non-Magnetic  Sur-Je5°C  Non-Magnetic  Sur-Je5°C  Non-Magnetic  - 125°C  Non-Magnetic  -125°C  Non-Magnetic  -125°	Tolerance	±5%
Operating Temperature Features Non-Magnetic  Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Sinon-Magnetic General Purpose	Voltage - Rated	1500V (1.5kV)
Features Non-Magnetic Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Temperature Coefficient	COG, NPO
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Features	Non-Magnetic
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case       1812 (4532 Metric)         Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.086" (2.18mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.086" (2.18mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	1812 (4532 Metric)
Thickness (Max) 0.086" (2.18mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.086" (2.18mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

### VJ1812A120JNRAR Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# VJ1812A120JNRAR Payment Methods





















### **VJ1812A120JNRAR Shipping Methods**













If you have any question about VJ1812A120JNRAR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com