



#### **VJ1812A150GNFAJ Information**

Heisener.com

Part Number VJ1812A150GNFAJ
Manufacturer Vishay Vitramon

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 15PF 2KV C0G/NP0 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VJ1812A150GNFAJ Specifications**

Manufacturer Part Number         VJ1812A150GNFAJ           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         1812 (4532 Metric)           Series         VJ           Capacitance         15pF           Tolerance         ±2%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -		
Category         Capacitors           Package         1812 (4532 Metric)           Series         VJ           Capacitance         15pF           Tolerance         ±2%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -	Manufacturer Part Number	VJ1812A150GNFAJ
Package         1812 (4532 Metric)           Series         VJ           Capacitance         15pF           Tolerance         ±2%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -	Manufacturer	Vishay Vitramon
Package         1812 (4532 Metric)           Series         VJ           Capacitance         15pF           Tolerance         ±2%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -	Category	Capacitors
Series         VJ           Capacitance         15pF           Tolerance         ±2%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -		Ceramic Capacitors
Capacitance 15pF Tolerance ±2%  Voltage - Rated 2000V (2kV)  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features Non-Magnetic  Ratings - Applications General Purpose  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm)  Lead Spacing -	Package	1812 (4532 Metric)
Tolerance         ±2%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -	Series	VJ
Voltage - Rated  2000V (2kV)  Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  Non-Magnetic  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  1812 (4532 Metric)  Size / Dimension  D.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max)  Thickness (Max)  0.086" (2.18mm)  Lead Spacing  -	Capacitance	15pF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  Non-Magnetic  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  1812 (4532 Metric)  Size / Dimension  0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max)  - Thickness (Max)  0.086" (2.18mm)  Lead Spacing  -  COG, NP0  COG, NP0  COG, NP0  COG, NP0  Cogneral Purpose  Failure  Rate  - 0.086" (2.18mm)  - COG, NP0  CO	Tolerance	±2%
Operating Temperature-55°C ~ 125°CFeaturesNon-MagneticRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-	Voltage - Rated	2000V (2kV)
FeaturesNon-MagneticRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Features	Non-Magnetic
Failure Rate  Mounting Type  Surface Mount, MLCC  Package / Case  1812 (4532 Metric)  Size / Dimension  0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max)  -  Thickness (Max)  0.086" (2.18mm)  Lead Spacing  -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Applications	General Purpose
Package / Case       1812 (4532 Metric)         Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.086" (2.18mm)         Lead Spacing       -	Failure Rate	-
Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.086" (2.18mm)         Lead Spacing       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  -  0.086" (2.18mm)  -	Package / Case	1812 (4532 Metric)
Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.086" (2.18mm)
Load Strile	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

#### VJ1812A150GNFAJ Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **VJ1812A150GNFAJ Payment Methods**



















## **VJ1812A150GNFAJ Shipping Methods**













If you have any question about VJ1812A150GNFAJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com