

VJ1825A123JBCAT4X

VJ1825A123JBCAT4X Information



For Reference Only

Part Number VJ1825A123JBCAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.012UF 200V NP0 1825

Package 1825 (4564 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1825A123JBCAT4X Specifications

Manufacturer Part Number VJ1825A123JBCAT4X Manufacturer Vishay Vitramon Category Capacitors Package 1825 (4564 Metric) Series VJ OMD Capacitance 0.012µF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -		
Category Capacitors Package 1825 (4564 Metric) Series VJ OMD Capacitance 0.012µF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Manufacturer Part Number	VJ1825A123JBCAT4X
Ceramic Capacitors Package 1825 (4564 Metric) Series VJ OMD Capacitance 0.012μF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Manufacturer	Vishay Vitramon
Package 1825 (4564 Metric) Series VJ OMD Capacitance 0.012μF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Category	Capacitors
Series VJ OMD Capacitance 0.012μF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -		Ceramic Capacitors
Capacitance0.012μFTolerance±5%Voltage - Rated200 VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.183" L x 0.252" W (4.65mm x 6.40mm)Height - Seated (Max)-	Package	1825 (4564 Metric)
Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Series	VJ OMD
Voltage - Rated Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension Height - Seated (Max) - COG, NP0 -55°C ~ 125°C -55°C ~ 125°C -50°C ~ 125°C -50°C ~ 125°C -105°C -1	Capacitance	0.012μF
Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Voltage - Rated	200V
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Temperature Coefficient	COG, NPO
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Applications	Boardflex Sensitive
Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Failure Rate	-
Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) -	Package / Case	1825 (4564 Metric)
	Size / Dimension	0.183" L x 0.252" W (4.65mm x 6.40mm)
0.00 (11.00)	Height - Seated (Max)	-
Thickness (Max) 0.086" (2.18mm)	Thickness (Max)	0.086" (2.18mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors		Report errors?

VJ1825A123JBCAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1825A123JBCAT4X Payment Methods



















VJ1825A123JBCAT4X Shipping Methods













If you have any question about VJ1825A123JBCAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com