

VJ1825A680KBAAT4X

VJ1825A680KBAAT4X Information



For Reference Only

Part Number VJ1825A680KBAAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 68PF 50V NP0 1825

Package 1825 (4564 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1825A680KBAAT4X Specifications

Manufacturer Part Number VJ1825A680KBAAT4X Manufacturer Vishay Vitramon Category Capacitors Package 1825 (4564 Metric) Series VJ OMD Capacitance 68pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L. x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1825 (4564 Metric) Series VJ OMD Capacitance 68pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Manufacturer Part Number	VJ1825A680KBAAT4X
Package 1825 (4564 Metric) Series VJ OMD Capacitance 68pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Manufacturer	Vishay Vitramon
Package 1825 (4564 Metric) Series VJ OMD Capacitance 68pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Category	Capacitors
Series VJ OMD Capacitance 68pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -		Ceramic Capacitors
Capacitance68pFTolerance±10%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.183" L x 0.252" W (4.65mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-	Package	1825 (4564 Metric)
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Series	VJ OMD
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.183" L x 0.252" W (4.65mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-	Capacitance	68pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing COG, NPO COG, NPO COG, NPO Soft Termination, High Voltage Soft Termination, High Voltage Soft Termination, High Voltage Soft Termination, High Voltage 10.183° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.183° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.183° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.183° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.183° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.183° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.183° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.183° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.184° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.185° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.186° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.186° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.186° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.186° L x 0.252° W (4.65mm x 6.40mm) - COG, NPO 10.186° L x 0.252° W (4.65mm x 6.40mm)	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Voltage - Rated	50V
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Temperature Coefficient	C0G, NP0
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Applications	Boardflex Sensitive
Package / Case 1825 (4564 Metric) Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.183" L x 0.252" W (4.65mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.086" (2.18mm) -	Package / Case	1825 (4564 Metric)
Thickness (Max) 0.086" (2.18mm) Lead Spacing -	Size / Dimension	0.183" L x 0.252" W (4.65mm x 6.40mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.086" (2.18mm)
Lead Style -	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

VJ1825A680KBAAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1825A680KBAAT4X Payment Methods



















VJ1825A680KBAAT4X Shipping Methods













If you have any question about VJ1825A680KBAAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com