

## **VJ2225Y183JBRAT4X**

### VJ2225Y183JBRAT4X Information



For Reference Only

Part Number VJ2225Y183JBRAT4X

Manufacturer Vishay Vitramon

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 0.018UF 1.5KV X7R 2225

**Package** 2225 (5763 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VJ2225Y183JBRAT4X Specifications**

Manufacturer Part Number         V12225Y183JBRAT4X           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         2225 (5763 Metric)           Series         VJ OMD           Capacitance         0.018µF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         2225 (5763 Metric)           Size / Dimension         0.226" L x 0.250" W (5.74mm x 6.35mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         2225 (5763 Metric)           Series         VJ OMD           Capacitance         0.018µF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         2225 (5763 Metric)           Size / Dimension         0.226" L x 0.250" W (5.74mm x 6.35mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	VJ2225Y183JBRAT4X
Package         2225 (5763 Metric)           Series         VJ OMD           Capacitance         0.018μF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         2225 (5763 Metric)           Size / Dimension         0.226" L x 0.250" W (5.74mm x 6.35mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Vishay Vitramon
Package         2225 (5763 Metric)           Series         VJ OMD           Capacitance         0.018µF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         2225 (5763 Metric)           Size / Dimension         0.226" L x 0.250" W (5.74mm x 6.35mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         VJ OMD           Capacitance         0.018µF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         2225 (5763 Metric)           Size / Dimension         0.226" L x 0.250" W (5.74mm x 6.35mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         0.018μF           Tolerance         ±5%           Voltage - Rated         1500V (1.5kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         2225 (5763 Metric)           Size / Dimension         0.226" L x 0.250" W (5.74mm x 6.35mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Package	2225 (5763 Metric)
Tolerance ±5%  Voltage - Rated 1500V (1.5kV)  Temperature Coefficient X7R  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings - Applications Boardflex Sensitive  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 2225 (5763 Metric)  Size / Dimension 0.226" L x 0.250" W (5.74mm x 6.35mm)  Height - Seated (Max) -  Thickness (Max) 0.086" (2.18mm)  Lead Spacing -  Lead Style -	Series	VJ OMD
Voltage - Rated  Temperature Coefficient  X7R  Operating Temperature  -55°C ~ 125°C  Features  Soft Termination, High Voltage  Ratings  - Applications  Boardflex Sensitive  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  2225 (5763 Metric)  Size / Dimension  0.226" L x 0.250" W (5.74mm x 6.35mm)  Height - Seated (Max)  - Thickness (Max)  0.086" (2.18mm)  Lead Spacing  - Lead Style	Capacitance	0.018μF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  Soft Termination, High Voltage  Ratings  - Applications  Boardflex Sensitive  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  2225 (5763 Metric)  Size / Dimension  0.226" L x 0.250" W (5.74mm x 6.35mm)  Height - Seated (Max)  Thickness (Max)  0.086" (2.18mm)  Lead Spacing  - Lead Style	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.226" L x 0.250" W (5.74mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Voltage - Rated	1500V (1.5kV)
Features Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.226" L x 0.250" W (5.74mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.226" L x 0.250" W (5.74mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.226" L x 0.250" W (5.74mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.226" L x 0.250" W (5.74mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 2225 (5763 Metric) Size / Dimension 0.226" L x 0.250" W (5.74mm x 6.35mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case       2225 (5763 Metric)         Size / Dimension       0.226" L x 0.250" W (5.74mm x 6.35mm)         Height - Seated (Max)       -         Thickness (Max)       0.086" (2.18mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.226" L x 0.250" W (5.74mm x 6.35mm)         Height - Seated (Max)       -         Thickness (Max)       0.086" (2.18mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	2225 (5763 Metric)
Thickness (Max) 0.086" (2.18mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.226" L x 0.250" W (5.74mm x 6.35mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.086" (2.18mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### VJ2225Y183JBRAT4X Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### VJ2225Y183JBRAT4X Payment Methods



















## VJ2225Y183JBRAT4X Shipping Methods













If you have any question about VJ2225Y183JBRAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com