

VLED150W-214-C0700-D-HV

VLED150W-214-C0700-D-HV Information



For Reference Only

Part Number VLED150W-214-C0700-D-HV
Manufacturer Thomas Research Products

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRVR CC AC/DC 107-214V 700MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VLED150W-214-C0700-D-HV Specifications

Manufacturer Part Number VLED150W-214-C0700-D-HV Manufacturer Thomas Research Products Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series VLED-150W-HV Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 312VAC Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)		
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series VLED-150W-HV Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 312VAC Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Manufacturer Part Number	VLED150W-214-C0700-D-HV
LED Drivers Package - Series VLED-150W-HV Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 312VAC Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Manufacturer	Thomas Research Products
Package - Series VLED-150W-HV Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 312VAC Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series VLED-150W-HV Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 312VAC Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)		LED Drivers
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 312VAC Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Package	-
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 312VAC Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Series	VLED-150W-HV
Number of Outputs 1 Voltage - Input (Min) 312VAC Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Туре	Constant Current
Voltage - Input (Min) Voltage - Input (Max) 512VAC Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature Efficiency 91% Termination Style Size / Dimension 312VAC 404V 404V	Topology	AC DC Converter
Voltage - Input (Max) Voltage - Output 107 ~ 214 V Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature Efficiency 91% Termination Style Size / Dimension 512VAC 107 ~ 214 V 107 ~ 214 V 108 ~ 214 V 109 ~ 2	Number of Outputs	1
Voltage - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Voltage - Input (Min)	312VAC
Current - Output (Max) 700mA Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Voltage - Input (Max)	512VAC
Power (Watts) 150W Voltage - Isolation - Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 150W - Company	Voltage - Output	107 ~ 214 V
Voltage - Isolation Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature	Current - Output (Max)	700mA
Dimming Analog Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Power (Watts)	150W
Features OTP, OVP, SCP Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Voltage - Isolation	-
Ratings IP67 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Dimming	Analog
Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Features	OTP, OVP, SCP
Efficiency 91% Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Ratings	IP67
Termination Style Wire Leads Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Operating Temperature	-
Size / Dimension 7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)	Efficiency	91%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	7.24" L x 3.46" W x 1.71" H (184.0mm x 88.0mm x 43.5mm)
		Report errors?

VLED150W-214-C0700-D-HV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VLED150W-214-C0700-D-HV Payment Methods





















VLED150W-214-C0700-D-HV Shipping Methods













If you have any question about VLED150W-214-C0700-D-HV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com