

**VLS3012HBX-2R2M Information**


For Reference Only

**Part Number** [VLS3012HBX-2R2M](#)  
**Manufacturer** TDK Corporation  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** INDUCTORS FOR POWER CIRCUITS, WO  
**Package** Nonstandard  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**VLS3012HBX-2R2M Specifications**

Manufacturer Part Number	<a href="#">VLS3012HBX-2R2M</a>
Manufacturer	TDK Corporation
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	Nonstandard
Series	VLS-HBX
Type	Wirewound
Material - Core	Metal
Inductance	2.2μH
Tolerance	±20%
Current Rating	3.15A
Current - Saturation	3.35A
Shielding	Shielded
DC Resistance (DCR)	106 mOhm Max
Q @ Freq	-
Frequency - Self Resonant	-
Ratings	-
Operating Temperature	-40°C ~ 105°C
Frequency - Test	1MHz
Features	-
Mounting Type	Surface Mount
Package / Case	Nonstandard
Supplier Device Package	-
Size / Dimension	0.117" L x 0.117" W (3.00mm x 3.00mm)

Height - Seated (Max)

0.047" (1.20mm)

[Report errors?](#)

## VLS3012HBX-2R2M Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## VLS3012HBX-2R2M Payment Methods



## VLS3012HBX-2R2M Shipping Methods



If you have any question about VLS3012HBX-2R2M, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)