

VMS-60-48 Information



For Reference Only

Part Number VMS-60-48 **Manufacturer** CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 60W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









~		. ~	• ~•	
VMS-	.60-48	3 Spe	ecific	ations

Manufacturer Part Number VMS-60-48 Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VMS-60 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VMS-60 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Manufacturer Part Number	VMS-60-48	
Package - Series VMS-60 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Manufacturer	CUI Inc.	
Package - Series VMS-60 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series VMS-60 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)		AC DC Converters	
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Package	-	
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Series	VMS-60	
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Туре	Open Frame	
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Medical Voltage - Isolation Sice / Dimension 48V 48V 48V 48V 48V 48V 48V 48	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Medical Voltage - Isolation Size / Dimension - Size / Dimension - Current - Output (Max)	Voltage - Input	90 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation Size / Dimension -20°C ~ 70°C (With Derating) Chassis Mount 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Voltage - Output 1	48V	
Voltage - Output 4 Current - Output (Max) 1.25A Power (Watts) 60W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Voltage - Output 2	-	
Current - Output (Max) 1.25A Power (Watts) Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 1.25A 1.25A 1.25A 60W Adjustable Medical 5.656kV (5656V) 90% Chisain Derating Chassis Mount 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Voltage - Output 3	-	
Power (Watts) Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Voltage - Output 4	-	
ApplicationsMedicalVoltage - Isolation $5.656kV (5656V)$ Efficiency 90% Operating Temperature $-20^{\circ}C \sim 70^{\circ}C \text{ (With Derating)}$ FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension 4.00° L x 2.00° W x 1.10° H (101.6 mm x 50.8 mm x 27.9 mm)	Current - Output (Max)	1.25A	
Voltage - Isolation 5.656kV (5656V) Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Power (Watts)	60W	
Efficiency 90% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Applications	Medical	
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Voltage - Isolation	5.656kV (5656V)	
Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Efficiency	90%	
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Operating Temperature	-20°C ~ 70°C (With Derating)	
Size / Dimension 4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	Features	Adjustable Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	4.00" L x 2.00" W x 1.10" H (101.6mm x 50.8mm x 27.9mm)	
		Report errors?	

VMS-60-48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VMS-60-48 Payment Methods





















VMS-60-48 Shipping Methods













If you have any question about VMS-60-48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com