

VMS-80-36 Information

For Reference Only

Part Number VMS-80-36 **Manufacturer** CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 36V 80W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TAME	00 26	C	: c:	4:
VMS-	-80-30	Spec	mca	uons

Manufacturer Part Number VMS-80-36 Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series VMS-80 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VMS-80 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Manufacturer Part Number	VMS-80-36	
Package - Series VMS-80 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Manufacturer	CUI Inc.	
Package - Series VMS-80 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series VMS-80 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)		AC DC Converters	
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Package	-	
Number of Outputs 1 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Series	VMS-80	
Voltage - Input 90 ~ 260 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Type	Open Frame	
Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.22A Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) -	Voltage - Input	90 ~ 260 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) - Current - Output (Max)	Voltage - Output 1	36V	
Voltage - Output 4 Current - Output (Max) 2.22A Power (Watts) Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature O°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Output 2	-	
Current - Output (Max) 2.22A Power (Watts) Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 2.22A 2.22A 80W Medical 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Universal Input Chassis Mount 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Voltage - Output 3	-	
Power (Watts) 80W Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Voltage - Output 4	-	
Applications Medical Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Current - Output (Max)	2.22A	
Voltage - Isolation 5.656kV (5656V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Power (Watts)	80W	
Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Applications	Medical	
Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Voltage - Isolation	5.656kV (5656V)	
Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Efficiency	85%	
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	
Size / Dimension 5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	Features	Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.01" W x 1.10" H (127.0mm x 76.5mm x 27.9mm)	
		Report errors?	

VMS-80-36 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VMS-80-36 Payment Methods



















VMS-80-36 Shipping Methods













If you have any question about VMS-80-36, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com