

VOF-15B-S48 Information

For Reference Only

Part Number VOF-15B-S48

Manufacturer CUI Inc.

Category Power Supplies - Board Mount

AC DC Converters

Description AC DC CONVERTER 48V 15W

Package 4-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VOF-15B-S48 Specifications

Manufacturer Part Number VOF-15B-848 Manufacturer CUI Inc. Category Power Supplies - Board Mount AC DC Converters Package 4-DIP Module Series VOF-15B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	-	
Category Power Supplies - Board Mount AC DC Converters Package 4-DIP Module Series VOF-15B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Manufacturer Part Number	VOF-15B-S48
Package 4-DIP Module Series VOF-15B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Manufacturer	CUI Inc.
Package 4-DIP Module Series VOF-15B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Category	Power Supplies - Board Mount
Series VOF-15B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25 °C ~ 70 °C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Package	4-DIP Module
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Series	VOF-15B
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Туре	Open Frame
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 320mA Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Features OCP, OVP, SCP Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension - Current - Output (Max) - Current - Output (Max) 320mA - Current - Output (Max) 320mA - Current - Output (Max) 15W Commercial) F(Commercial) F(Commercial) F(Commercial) F(Commercial) F(Commercial) F(Commercial) T(Commercial) F(Commercial) T(Commercial) F(Commercial) T(Commercial) F(Commercial) T(Commercial) F(Commercial) F(Com	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Features OCP, OVP, SCP Operating Temperature Efficiency 84.63% Mounting Type Through Hole Package / Case Size / Dimension - United Size / Dimension Size / Dimension - Output (Max) - Commercial - Commerci	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension -320mA -250mA OCP, OVP, SCP OCP, OVP, SCP -25°C ~ 70°C (With Derating) 84.63% Mounting Type Through Hole 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 320mA 320mA 15W 15W 15W 15W 15W 15W 15W 15	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 15W ITE (Commercial) OCP, OVP, SCP (With Derating) Features -25°C ~ 70°C (With Derating) 84.63% Mounting Type Through Hole 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Voltage - Output 4	-
Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Current - Output (Max)	320mA
Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Power (Watts)	15W
Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Applications	ITE (Commercial)
Efficiency 84.63% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Features	OCP, OVP, SCP
Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Operating Temperature	-25°C ~ 70°C (With Derating)
Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Efficiency	84.63%
Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Mounting Type	Through Hole
	Package / Case	4-DIP Module
Report errors?	Size / Dimension	2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)
		Report errors?

VOF-15B-S48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VOF-15B-S48 Payment Methods



















VOF-15B-S48 Shipping Methods













If you have any question about VOF-15B-S48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com