

### **VOF-15B-S5 Information**



For Reference Only

Part Number VOF-15B-S5
Manufacturer CUI Inc.

**Category** Power Supplies - Board Mount

AC DC Converters

**Description** AC DC CONVERTER 5V 15W

Package 4-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VOF-15B-S5 Specifications**

Manufacturer Part Number         VOF-15B-S5           Manufacturer         CUI Inc.           Category         Power Supplies - Board Mount           AC DC Converters           Package         4-DIP Module           Series         VOF-15B           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         15W           Applications         ITE (Commercial)           Features         OCP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         81.37%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	-	
Category         Power Supplies - Board Mount           AC DC Converters           Package         4-DIP Module           Series         VOF-15B           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         15W           Applications         ITE (Commercial)           Features         OCP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         81.37%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Manufacturer Part Number	VOF-15B-S5
Package         4-DIP Module           Series         VOF-15B           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         15W           Applications         ITE (Commercial)           Features         OCP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         81.37%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Manufacturer	CUI Inc.
Package         4-DIP Module           Series         VOF-15B           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         15W           Applications         ITE (Commercial)           Features         OCP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         81.37%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Category	Power Supplies - Board Mount
Series         VOF-15B           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         15W           Applications         ITE (Commercial)           Features         OCP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         81.37%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         15W           Applications         ITE (Commercial)           Features         OCP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         81.37%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Package	4-DIP Module
Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         15W           Applications         ITE (Commercial)           Features         OCP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         81.37%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Series	VOF-15B
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.8A           Power (Watts)         15W           Applications         ITE (Commercial)           Features         OCP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         81.37%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Туре	Open Frame
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.8A Power (Watts) 15W Applications ITE (Commercial) Features OCP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 81.37% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  Features  OCP, OVP, SCP  Operating Temperature  Efficiency  81.37%  Mounting Type  Through Hole  Package / Case  Size / Dimension  - Current - Output (Max)  - Curr	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       2.8A         Power (Watts)       15W         Applications       ITE (Commercial)         Features       OCP, OVP, SCP         Operating Temperature       -25°C ~ 70°C (With Derating)         Efficiency       81.37%         Mounting Type       Through Hole         Package / Case       4-DIP Module         Size / Dimension       2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Voltage - Output 1	5V
Voltage - Output 4  Current - Output (Max)  2.8A  Power (Watts)  15W  Applications  ITE (Commercial)  Features  OCP, OVP, SCP  Operating Temperature  -25°C ~ 70°C (With Derating)  Efficiency  81.37%  Mounting Type  Through Hole  Package / Case  4-DIP Module  Size / Dimension  -2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Voltage - Output 2	-
Current - Output (Max)  2.8A  Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OVP, SCP  Operating Temperature  -25°C ~ 70°C (With Derating)  Efficiency  81.37%  Mounting Type  Through Hole  Package / Case  4-DIP Module  Size / Dimension  2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Features  OCP, OVP, SCP  Operating Temperature  -25°C ~ 70°C (With Derating)  Efficiency  81.37%  Mounting Type  Through Hole  Package / Case  4-DIP Module  Size / Dimension  15W  ITE (Commercial)  OCP, OVP, SCP  -25°C ~ 70°C (With Derating)  Features  -25°C ~ 70°C (With Derating)	Voltage - Output 4	-
Applications ITE (Commercial)  Features OCP, OVP, SCP  Operating Temperature -25°C ~ 70°C (With Derating)  Efficiency 81.37%  Mounting Type Through Hole  Package / Case 4-DIP Module  Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Current - Output (Max)	2.8A
Features OCP, OVP, SCP  Operating Temperature -25°C ~ 70°C (With Derating)  Efficiency 81.37%  Mounting Type Through Hole  Package / Case 4-DIP Module  Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Power (Watts)	15W
Operating Temperature  -25°C ~ 70°C (With Derating)  Efficiency  81.37%  Mounting Type  Through Hole  Package / Case  4-DIP Module  Size / Dimension  2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Applications	ITE (Commercial)
Efficiency 81.37%  Mounting Type Through Hole  Package / Case 4-DIP Module  Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Features	OCP, OVP, SCP
Mounting Type Through Hole  Package / Case 4-DIP Module  Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Operating Temperature	-25°C ~ 70°C (With Derating)
Package / Case         4-DIP Module           Size / Dimension         2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Efficiency	81.37%
Size / Dimension 2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)	Mounting Type	Through Hole
	Package / Case	4-DIP Module
Report errors?	Size / Dimension	2.33" L x 1.67" W x 0.90" H (59.2mm x 42.3mm x 22.9mm)
		Report errors?

### **VOF-15B-S5 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **VOF-15B-S5 Payment Methods**



















## **VOF-15B-S5 Shipping Methods**













If you have any question about VOF-15B-S5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com