

### **VOF-185-15 Information**

Part Number VOF-185-15 Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 15V 111W/185W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VOF-185-15 Specifications**

Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         VOF-185           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 277 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.33A           Power (Watts)         111W (185W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         85%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         VOF-185           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 277 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.33A           Power (Watts)         111W (185W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         85%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Manufacturer Part Number	VOF-185-15	
AC DC Converters           Package         -           Series         VOF-185           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 277 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.33A           Power (Watts)         111W (185W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         85%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Manufacturer	CUI Inc.	
Package         -           Series         VOF-185           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 277 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.33A           Power (Watts)         111W (185W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         85%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         VOF-185           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 277 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.33A           Power (Watts)         111W (185W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         85%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)		AC DC Converters	
TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 277 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.33APower (Watts)111W (185W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Package	-	
Number of Outputs       1         Voltage - Input       90 ~ 277 VAC         Voltage - Output 1       15V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       12.33A         Power (Watts)       111W (185W Forced Air)         Applications       ITE (Commercial)         Voltage - Isolation       3kV (3000V)         Efficiency       85%         Operating Temperature       -20°C ~ 70°C (With Derating)         Features       Adjustable Output, PFC, Standby Output, Universal Input         Mounting Type       Chassis Mount         Size / Dimension       5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Series	VOF-185	
Voltage - Input  90 ~ 277 VAC  Voltage - Output 1  15V  Voltage - Output 2  - Voltage - Output 3  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  95%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Size / Dimension  5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Type	Open Frame	
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  Voltage - Isolation  Styler (3000V)  Efficiency  Operating Temperature  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Size / Dimension  15V  - Output (2  - Courtent - Output (3  - Current - Output (4  - Current - Output (Max)  12.33A  111W (185W Forced Air)  111W (185W Forced Air)  112 (Commercial)  3kV (3000V)  85%  Operating Temperature  - 20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Number of Outputs	1	
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Output 3  - Chassis Mount  - Commercial (With Derating)  - Chassis Mount  - Chas	Voltage - Input	90 ~ 277 VAC	
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Output 4  - Commercial  - Commercial  3kV (3000V)  - Commercial  4kV (3000V)  - Commercial  5kV (300	Voltage - Output 1	15V	
Voltage - Output 4-Current - Output (Max)12.33APower (Watts)111W (185W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Voltage - Output 2	-	
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  SkV (3000V)  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  12.33A  111W (185W Forced Air)  ITE (Commercial)  SkV (3000V)  85%  Operating Temperature  -20°C ~ 70°C (With Derating)  Adjustable Output, PFC, Standby Output, Universal Input  Size / Dimension  5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Voltage - Output 3	-	
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  85%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 85%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Current - Output (Max)	12.33A	
Voltage - Isolation 3kV (3000V)  Efficiency 85%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Power (Watts)	111W (185W Forced Air)	
Efficiency 85%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Applications	ITE (Commercial)	
Operating Temperature  -20°C ~ 70°C (With Derating)  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Efficiency	85%	
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Operating Temperature	-20°C ~ 70°C (With Derating)	
Size / Dimension 5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	Features	Adjustable Output, PFC, Standby Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)	
			Report errors?

#### **VOF-185-15 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **VOF-185-15 Payment Methods**



















## **VOF-185-15 Shipping Methods**













If you have any question about VOF-185-15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com