

VOF-280-36 Information

Part Number VOF-280-36 Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 36V 168W/280W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VOF-280-36 Specifications

Manufacturer Part Number VOF-280-36 Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VOF-280 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 277 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VOF-280 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 277 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
AC DC Converters Package - Series VOF-280 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 277 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Package - Series VOF-280 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 277 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Series VOF-280 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 277 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 277 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Number of Outputs 1 Voltage - Input 90 ~ 277 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Voltage - Input 90 ~ 277 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 90 ~ 277 VAC 36V - 168V 168V
Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.78A Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Current - Output (Max) 7.78A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Power (Watts) 168W (280W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V)
Voltage - Isolation 3kV (3000V)
Efficiency 90%
Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Features Adjustable Output, PFC, Standby Output, Universal Input
Mounting Type Chassis Mount
Size / Dimension 5.00" L x 3.00" W x 1.38" H (127.0mm x 76.2mm x 35.0mm)
Report errors

VOF-280-36 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VOF-280-36 Payment Methods





















VOF-280-36 Shipping Methods













If you have any question about VOF-280-36, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com