

VPM48-2080

VPM48-2080 Information



Part Number	VPM48-2080	
Manufacturer	Triad Magnetics	
Category	Transformers Power Transformers	
Description	XFRMR 100VA MED GRADE CHASS MNT	
Package	-	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VPM48-2080 Specifications

Manufacturer Part NumberVPM48-2080ManufacturerTriad MagneticsCategoryTransformersPackage-SeriesToroidal Medical, VPMTypeToroidal Medical, VPMVoltage - Primary100V, 120V, 220V, 240VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)NoPower - MaxNoNouting TypeChassis MountSize / DimensionSize / DimensionSize / DimensionSizonmVoltage - IsolationSizonmWeightSize / DimensionKeightSize / DimensionManufingSizonmSoute - Soute - MaxSizonmSize / DimensionSizonmSize / DiagonSizonmSize / Diagon		
CategoryTransformersPackage-SeriesToroidal Medical, VPMTypeToroidal Medical, VPMVoltage - Primary100V, 120V, 220V, 240VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChasis MountSize / Dimension96.00mm DiaSize / Dimension52.00mmHeight - Seated (Max)52.00mmWeight2.7 lbs (1.2kg)	Manufacturer Part Number	VPM48-2080
InterfactPower TransformersPackage-SeriesToroidal Medical, VPMTypeToroidal Medical, VPMVoltage - Primary100V, 120V, 220V, 240VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChassis MountTermination StyleSize / DimensionSize / Dimension52.00mmHeight - Seated (Max)52.00mmVoltage - Isolation400VrmsWeightStri Leags	Manufacturer	Triad Magnetics
Package-SeriesToroidal Medical, VPMTypeToroidalVoltage - Primary100V, 120V, 220V, 240VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChasis MountSize / Dimension9600mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 Ibs (1.2kg)	Category	Transformers
SeriesToroidal Medical, VPMTypeToroidalYoltage - Primary100V, 120V, 220V, 240VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChasis MountSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)		Power Transformers
TypeToroidalVoltage - Primary100V, 120V, 220V, 240VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChassis MountTermination Style96.00mm DiaSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmWoltage - Isolation2.7 lbs (1.2kg)	Package	-
YVoltage - Primary100V, 120V, 220V, 240VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChasis MountTermination Style96.00mm DiaSize / Dimension52.00mmHeight - Seated (Max)52.00mmVoltage - Isolation27.1bs (1.2kg)	Series	Toroidal Medical, VPM
Voltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Туре	Toroidal
Current - Output (Max)Parallel 4.16A, Series 2.08APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Voltage - Primary	100V, 120V, 220V, 240V
Primary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Voltage - Secondary (Full Load)	Parallel 24V, Series 48V
Secondary Winding(s)DualCenter TapNoPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Current - Output (Max)	Parallel 4.16A, Series 2.08A
Center TapNoPower - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight5.7 lbs (1.2kg)	Primary Winding(s)	Dual, Multiple Taps
Power - Max100 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Secondary Winding(s)	Dual
Mounting TypeChassis MountTermination StyleWire LeadsSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Center Tap	No
Termination StyleWire LeadsSize / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Power - Max	100 VA
Size / Dimension96.00mm DiaHeight - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Mounting Type	Chassis Mount
Height - Seated (Max)52.00mmVoltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Termination Style	Wire Leads
Voltage - Isolation4000VrmsWeight2.7 lbs (1.2kg)	Size / Dimension	96.00mm Dia
Weight 2.7 lbs (1.2kg)	Height - Seated (Max)	52.00mm
	Voltage - Isolation	4000Vrms
	Weight	2.7 lbs (1.2kg)
Report errors?		Report errors?

VPM48-2080 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

VPM48-2080 Payment Methods Image: I

If you have any question about VPM48-2080, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com