

VPP12-200

VPP12-200 Information



Part Number	VPP12-200	
Manufacturer	Triad Magnetics	
Category	Transformers Power Transformers	
Description	XFRMR LAMINATED 2.5VA THRU HOLE	
Package	-	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VPP12-200 Specifications

ManufacturerTriad MagneticsCategoryTransformersPower TransformersPower TransformersPackage-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation4000Vrms		
CategoryTransformersPower TransformersPackagePackageSeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmWeight0.00VrmsWeight0.25 lb (113.4g)	Manufacturer Part Number	VPP12-200
PackagePower TransformersPackage-SeriesPC Mourt: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmWeight0.25 lb (113.4g)	Manufacturer	Triad Magnetics
Package-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmWoitget - Isolation4000VrmsWeight0.25 lb (113.4g)	Category	Transformers
SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmWeight0.00VrmsWeight0.25 lb (113.4g)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)88.58mmWotage - Isolation0.00VrmsWeight0.25 lb (113.4g)	Package	-
Voltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)85.58mmWoltage - Isolation0.25 Ib (113.4g)	Series	PC Mount: World Series?
Voltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmWoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Туре	Laminated Core
Current - Output (Max)Parallel 400mA, Series 200mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation0.25 lb (113.4g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Current - Output (Max)	Parallel 400mA, Series 200mA
Center TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Primary Winding(s)	Dual
Power - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Center Tap	No
Termination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Power - Max	2.5 VA
Size / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)28.58mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Mounting Type	Through Hole
Height - Seated (Max)28.58mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Termination Style	PC Pin
Voltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Size / Dimension	41.28mm L x 33.32mm W
Weight 0.25 lb (113.4g)	Height - Seated (Max)	28.58mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	0.25 lb (113.4g)
•		Report errors?

VPP12-200 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about VPP12-200, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com