

VPP20-2800-B Information



For Reference Only

Part Number VPP20-2800-B

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description XFRMR LAMINATED 56VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VPP20-2800-B Specifications

Manufacturer Part NumberVPP20-2800-BManufacturerTriad MagneticsCategoryTransformersPackage-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 5.6A, Series 2.8APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension76.20mm L x 63.50mm W		
Category Power Transformers Package PC Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 5.6A, Series 2.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Package PC Mount: World Series? PC Mount: World Serie	Manufacturer Part Number	VPP20-2800-B
Package - Series PC Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 5.6A, Series 2.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Triad Magnetics
Package - PC Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 5.6A, Series 2.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin	Category	Transformers
SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 5.6A, Series 2.8APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC Pin		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 5.6A, Series 2.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 5.6A, Series 2.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style	Series	PC Mount: World Series?
Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 5.6A, Series 2.8APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC Pin	Туре	Laminated Core
Current - Output (Max) Parallel 5.6A, Series 2.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Secondary Winding Type Through Hole Termination Style Parallel 5.6A, Series 2.8A Dual Pual Pual Pual Pual Pual Pual Pual P	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Dual No Poul Pou	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)DualCenter TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC Pin	Current - Output (Max)	Parallel 5.6A, Series 2.8A
Center TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC Pin	Primary Winding(s)	Dual
Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin	Center Tap	No
Termination Style PC Pin	Power - Max	56 VA
	Mounting Type	Through Hole
Size / Dimension 76.20mm L x 63.50mm W	Termination Style	PC Pin
	Size / Dimension	76.20mm L x 63.50mm W
Height - Seated (Max) 46.02mm	Height - Seated (Max)	46.02mm
Voltage - Isolation 4000Vrms	Voltage - Isolation	4000Vrms
Weight 1.7 lbs (771.1g)	Weight	1.7 lbs (771.1g)
Report errors?		Report errors?

VPP20-2800-B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VPP20-2800-B Payment Methods



















VPP20-2800-B Shipping Methods













If you have any question about VPP20-2800-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com