

VPP28-1060

VPP28-1060 Information



Part Number	VPP28-1060	
Manufacturer	Triad Magnetics	
Category	Transformers Power Transformers	
Description	XFRMR LAMINATED 30VA THRU HOLE	
Package	-	
	For the pricing/inventory/lead time, please contact	
	us Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VPP28-1060 Specifications

Manufacturer Part NumberVPP28-1060ManufacturerTriad MagneticsCategoryTransformersPower TransformersPower TransformersPackage-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm Lx 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeightLa by (Set4.3g)		
CategoryTransformersPackage-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation1.2 lbs (544.3g)	Manufacturer Part Number	VPP28-1060
IntegrationPower TransformersPackage-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StyleSecondary LSize / Dimension6.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Manufacturer	Triad Magnetics
Package.SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeFrong HoleSize / Dimension6.68mm Lx 55.55mm WHeight - Seated (Max)9.07mmVoltage - Isolation400VrmsWeight1.2 lbs (544.3g)	Category	Transformers
SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination Style6.68mm L x 55.55mm WSize / Dimension39.67mmHeight - Seated (Max)39.07mmWeight1.2 lbs (544.3g)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination Style66.68mm L x 55.55mm WSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.07mmVoltage - Isolation1.2 lbs (544.3g)	Package	-
SystemInterferenceVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination Style66.68mm L x 55.55mm WSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmWoltage - Isolation1.2 lbs (544.3g)	Series	PC Mount: World Series?
Voltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination Style66.68mm L x 55.55mm WSize / Dimension39.67mmHeight - Seated (Max)39.07mmWoltage - Isolation1.2 lbs (544.3g)	Туре	Laminated Core
Current - Output (Max)Parallel 2.12A, Series 1.06APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation1.2 lbs (544.3g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Voltage - Secondary (Full Load)	Parallel 14V, Series 28V
Secondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Current - Output (Max)	Parallel 2.12A, Series 1.06A
Center TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Primary Winding(s)	Dual
Power - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Center Tap	No
Termination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Power - Max	30 VA
Size / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Mounting Type	Through Hole
Height - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Termination Style	PC Pin
Voltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Size / Dimension	66.68mm L x 55.55mm W
Weight 1.2 lbs (544.3g)	Height - Seated (Max)	39.67mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	1.2 lbs (544.3g)
		Report errors?

VPP28-1060 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about VPP28-1060, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com