

VPS10-2500-B Information

Heisener.com

For Reference Only

Part Number VPS10-2500-B
Manufacturer Triad Magnetics
Category Transformers
Power Transformers

Description XFRMR LAMINATED 25VA CHAS MOUNT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VPS10-2500-B Specifications

Manufacturer Part NumberVPS10-2500-BManufacturerTriad MagneticsCategoryTransformersPower TransformersPower TransformersPackage-SeriesChassis Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 5A, Series 2.5APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension50.80mm L x 49.28mm W		
Category Transformers Power Transformers Package Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style	Manufacturer Part Number	VPS10-2500-B
Package Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Series Solder, Quick Connect	Manufacturer	Triad Magnetics
Package - Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 25 VA Mounting Type Chassis Mount Termination Style Science 2.5A	Category	Transformers
Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 25 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 25 VA Mounting Type Chassis Mount Termination Style Laminated Core Laminated Core No Parallel 5V, Series 10V Parallel 5A, Series 2.5A Primary Winding(s) Dual Center Tap No Solder, Quick Connect	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 25 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect	Series	Chassis Mount: World Series?
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5V, Series 10V Parallel 5A, Series 2.5A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 25 VA Mounting Type Chassis Mount Termination Style Parallel 5V, Series 10V Parallel 5A, Series 2.5A Dual Secondary Winding(s) Dual Secondary Winding(s) Solder, Quick Connect	Туре	Laminated Core
Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 25 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Termination Style Dual No 25 VA Mounting Type Chassis Mount Solder, Quick Connect	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s) Center Tap No Power - Max 25 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect	Current - Output (Max)	Parallel 5A, Series 2.5A
Center TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleSolder, Quick Connect	Primary Winding(s)	Dual
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Solder, Quick Connect	Center Tap	No
Termination Style Solder, Quick Connect	Power - Max	25 VA
	Mounting Type	Chassis Mount
Size / Dimension 50.80mm L x 49.28mm W	Termination Style	Solder, Quick Connect
	Size / Dimension	50.80mm L x 49.28mm W
Height - Seated (Max) 58.67mm	Height - Seated (Max)	58.67mm
Voltage - Isolation 4000Vrms	Voltage - Isolation	4000Vrms
Weight 1.3 lbs (589.7g)	Weight	1.3 lbs (589.7g)
Report errors?		Report errors?

VPS10-2500-B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VPS10-2500-B Payment Methods



















VPS10-2500-B Shipping Methods













If you have any question about VPS10-2500-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com