

VPS12-3400-B Information

Heisener.com

Part Number VPS12-3400-B
Manufacturer Triad Magnetics
Category Transformers
Power Transformers

Description XFRMR LAMINATED 43VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VPS12-3400-B Specifications

Manufacturer Part Number VPS12-3400-B Manufacturer Triad Magnetics Category Transformers Package - Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 6.8A, Series 3.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) 68.33mm Voltage - Isolation 4000Vrms Weight 1.6 lbs (725.7g)		
CategoryTransformersPower TransformersPackage-SeriesChassis Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 6.8A, Series 3.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max43 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension58.67mm L x 50.80mm WHeight - Seated (Max)68.33mmVoltage - Isolation4000VrmsWeight1.6 lbs (725.7g)	Manufacturer Part Number	VPS12-3400-B
Package - Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Size / Dimension Size / Dimension Height - Seated (Max) Weight World Series Chassis Mount Fransformers Power Transformers Laminated Core Laminat	Manufacturer	Triad Magnetics
Package - Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 6.8A, Series 3.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) 68.33mm Voltage - Isolation 4000Vrms Weight	Category	Transformers
Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 6.8A, Series 3.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) 68.33mm Voltage - Isolation 4000Vrms Weight 1.6 lbs (725.7g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 6.8A, Series 3.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) 68.33mm Voltage - Isolation 4000Vrms Weight 1.6 lbs (725.7g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 6.8A, Series 3.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) Voltage - Isolation Weight 1.6 lbs (725.7g)	Series	Chassis Mount: World Series?
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 6.3V, Series 12.6V Parallel 6.8A, Series 3.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 6.3V, Series 12.6V Parallel 6.3V, Series 12.6V Solder Parallel 6.3V, Series 12.6V Solder Solder	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Size / Dimension Size / Dimension Woltage - Isolation Weight Parallel 6.8A, Series 3.4A Parallel 6.8A, Series 3.4A Pual Parallel 6.8A, Series 3.4A Pual Ray No Solde No Solde Sol	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 43 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) Voltage - Isolation 4000Vrms Weight 1.6 lbs (725.7g)	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)DualCenter TapNoPower - Max43 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension58.67mm L x 50.80mm WHeight - Seated (Max)68.33mmVoltage - Isolation4000VrmsWeight1.6 lbs (725.7g)	Current - Output (Max)	Parallel 6.8A, Series 3.4A
Center TapNoPower - Max43 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension58.67mm L x 50.80mm WHeight - Seated (Max)68.33mmVoltage - Isolation4000VrmsWeight1.6 lbs (725.7g)	Primary Winding(s)	Dual
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) 68.33mm Voltage - Isolation 4000Vrms Weight 1.6 lbs (725.7g)	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) 68.33mm Voltage - Isolation 4000Vrms Weight 1.6 lbs (725.7g)	Center Tap	No
Termination Style Solder, Quick Connect Size / Dimension 58.67mm L x 50.80mm W Height - Seated (Max) 68.33mm Voltage - Isolation 4000Vrms Weight 1.6 lbs (725.7g)	Power - Max	43 VA
Size / Dimension58.67mm L x 50.80mm WHeight - Seated (Max)68.33mmVoltage - Isolation4000VrmsWeight1.6 lbs (725.7g)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Weight 68.33mm 4000Vrms 1.6 lbs (725.7g)	Termination Style	Solder, Quick Connect
Voltage - Isolation 4000Vrms Weight 1.6 lbs (725.7g)	Size / Dimension	58.67mm L x 50.80mm W
Weight 1.6 lbs (725.7g)	Height - Seated (Max)	68.33mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	1.6 lbs (725.7g)
		Report errors?

VPS12-3400-B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VPS12-3400-B Payment Methods



















VPS12-3400-B Shipping Methods













If you have any question about VPS12-3400-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com