

VPS230-570 Information



For Reference Only

Part Number VPS230-570

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description XFRMR LAMINATED 130VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VPS230-570 Specifications

Manufacturer Part Number Manufacturer Category Triad Magnetics Transformers Power Transformers Power Transformers Package - Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 115V, 230V Voltage - Secondary (Full Load) Parallel 1.14A, Series 230V Current - Output (Max) Parallel 1.14A, Series 570mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) Voltage - Isolation Weight 4.1 lbs (1.9kg)		
Category Power Transformers Power Transformers Package - Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 115V, Series 230V Current - Output (Max) Parallel 1.14A, Series 570mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) Voltage - Isolation 4000Vrms	Manufacturer Part Number	VPS230-570
Package - Chassis Mount: World Series? Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 115V, 230V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Nounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Power - Max Anounting Type Chassis Mount Winding(s) Solder, Quick Connect Go.45mm L x 68.33mm W Woltage - Isolation Power - Isolation	Manufacturer	Triad Magnetics
Package Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 115V, Series 230V Current - Output (Max) Parallel 1.14A, Series 570mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension Height - Seated (Max) Voltage - Isolation - Chassis Mount - Chassis Moun	Category	Transformers
Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 115V, Series 230V Current - Output (Max) Parallel 1.14A, Series 570mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 115V, Series 230V Current - Output (Max) Parallel 1.14A, Series 570mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Pual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation 115V, 230V Parallel 1.15V, Series 230V Parallel 1.14A, Series 570mA Parallel 1.14A, Series 570mA Parallel 1.14A, Series 570mA Parallel 1.14A, Series 570mA Parallel 1.14A, Series 230V Parallel 1.15V, 230V Parallel 1.15V, Series 230V	Series	Chassis Mount: World Series?
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 1.14A, Series 570mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Parallel 1.15V, Series 230V Parallel 1.14A, Series 570mA Dual Secondary Winding(s) Dual Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 40.45mm L x 68.33mm W Woltage - Isolation	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Parallel 1.14A, Series 570mA Dual Sual Center Size / Dual No Powal No Powal No Powal No Powal No Powal No Powal No No Powal No No Powal No No Powal No	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) Voltage - Isolation Dual No 4000Vrms	Voltage - Secondary (Full Load)	Parallel 115V, Series 230V
Secondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000Vrms	Current - Output (Max)	Parallel 1.14A, Series 570mA
Center TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000Vrms	Primary Winding(s)	Dual
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms	Center Tap	No
Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms	Power - Max	130 VA
Size / Dimension60.45mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000Vrms	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation 85.85mm 4000Vrms	Termination Style	Solder, Quick Connect
Voltage - Isolation 4000Vrms	Size / Dimension	60.45mm L x 68.33mm W
	Height - Seated (Max)	85.85mm
Weight 4.1 lbs (1.9kg)	Voltage - Isolation	4000Vrms
6	Weight	4.1 lbs (1.9kg)
Report errors?		Report errors?

VPS230-570 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VPS230-570 Payment Methods



















VPS230-570 Shipping Methods













If you have any question about VPS230-570, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com