

VPS24-5400-B Information

Heisener.com

For Reference Only

Part NumberVPS24-5400-BManufacturerTriad MagneticsCategoryTransformers

Power Transformers

Description XFRMR LAMINATED 130VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VPS24-5400-B Specifications

Manufacturer Part Number VPS24-5400-B Manufacturer Triad Magnetics Category Transformers Package - Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 10.8A, Series 5.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)		
CategoryTransformersPower TransformersPackage-SeriesChassis Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 10.8A, Series 5.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Manufacturer Part Number	VPS24-5400-B
Package - Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Seight Weight Power Transformers Chassis Mount Power Transformers Power Transformers Power Transformers Power Transformers A chassis Mount Series 24V Dual Dual Center Tap No Chassis Mount Secondary Winding(s) Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 40.45mm L x 68.33mm W Weight Voltage - Isolation 4000Vrms Weight	Manufacturer	Triad Magnetics
Package - Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 10.8A, Series 5.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms Weight	Category	Transformers
Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 10.8A, Series 5.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 10.8A, Series 5.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 10.8A, Series 5.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 115V, 230V Parallel 12V, Series 24V Parallel 10.8A, Series 5.4A Primary Winding(s) Dual Could Secondary Winding(s) Dual Contest Solder Output Chassis Mount Solder, Quick Connect 4000Vrms 4000Vrms 4000Vrms 41 lbs (1.9kg)	Series	Chassis Mount: World Series?
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 10.8A, Series 5.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 12V, Series 24V Parallel 10.8A, Series 5.4A Primary Winding (s) Dual No Chassis Mount Solder (Chassis Mount 4000 Vrms 4000 Vrms 4000 Vrms 41.1 lbs (1.9kg)	Туре	Laminated Core
Current - Output (Max) Parallel 10.8A, Series 5.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Current - Output (Max)	Parallel 10.8A, Series 5.4A
Center TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension60.45mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Primary Winding(s)	Dual
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)	Center Tap	No
Termination Style Solder, Quick Connect 60.45mm L x 68.33mm W Height - Seated (Max) 85.85mm Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)	Power - Max	130 VA
Size / Dimension60.45mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Weight 85.85mm 4000Vrms 4.1 lbs (1.9kg)	Termination Style	Solder, Quick Connect
Voltage - Isolation 4000Vrms Weight 4.1 lbs (1.9kg)	Size / Dimension	60.45mm L x 68.33mm W
Weight 4.1 lbs (1.9kg)	Height - Seated (Max)	85.85mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	4.1 lbs (1.9kg)
		Report errors?

VPS24-5400-B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VPS24-5400-B Payment Methods



















VPS24-5400-B Shipping Methods













If you have any question about VPS24-5400-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com