

## **VPS28-900 Information**



For Reference Only

Part Number VPS28-900

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

**Description** XFRMR LAMINATED 25VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VPS28-900 Specifications**

Manufacturer         VPS28-900           Manufacturer         Triad Magnetics           Category         Transformers           Power Transformers         Power Transformers           Package         -           Series         Chassis Mount: World Series?           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 14V, Series 28V           Current - Output (Max)         Parallel 1.8A, Series 900mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         25 VA           Mounting Type         Chassis Mount           Termination Style         Solder, Quick Connect           Size / Dimension         50.80mm L x 49.28mm W           Height - Seated (Max)         58.67mm           Voltage - Isolation         4000Vrms           Weight         1.3 lbs (559.7c)		
CategoryTransformersPackage-SeriesChassis Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 1.8A, Series 900mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension50.80mm L x 49.28mm WHeight - Seated (Max)58.67mmVoltage - Isolation4000Vrms	Manufacturer Part Number	VPS28-900
Package - Series Chassis Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 1.8A, Series 900mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 25 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 50.80mm L x 49.28mm W Height - Seated (Max) Voltage - Isolation 4000Vrms	Manufacturer	Triad Magnetics
Package - Chassis Mount: World Series?  Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 14V, Series 28V  Current - Output (Max) Parallel 1.8A, Series 900mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 25 VA  Mounting Type Chassis Mount  Termination Style Solder, Quick Connect  Size / Dimension 50.80mm L x 49.28mm W  Height - Seated (Max) 58.67mm  Voltage - Isolation 4000Vrms	Category	Transformers
Series Chassis Mount: World Series?  Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 14V, Series 28V  Current - Output (Max) Parallel 1.8A, Series 900mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 25 VA  Mounting Type Chassis Mount  Termination Style Solder, Quick Connect  Size / Dimension 50.80mm L x 49.28mm W  Height - Seated (Max) 58.67mm  Voltage - Isolation 4000Vrms		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 14V, Series 28V  Current - Output (Max) Parallel 1.8A, Series 900mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 25 VA  Mounting Type Chassis Mount  Termination Style Solder, Quick Connect  Size / Dimension 50.80mm L x 49.28mm W  Height - Seated (Max)  Voltage - Isolation 4000Vrms	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 14V, Series 28V  Current - Output (Max)  Parallel 1.8A, Series 900mA  Primary Winding(s)  Dual  Secondary Winding(s)  Center Tap  No  Power - Max  25 VA  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  50.80mm L x 49.28mm W  Height - Seated (Max)  Voltage - Isolation  115V, 230V  Parallel 14V, Series 28V  Parallel 1.8A, Series 900mA  Poual  Chashies 900mA  Dual  Secondary Winding(s)  Chashies 900mA  Dual  Secondary Winding(s)  Dual  Secondary Winding(s)  Dual  Secondary Winding(s)  Dual  Secondary Winding(s)  Solder Tap  No  Chassis Mount  Termination Style  Solder, Quick Connect  Size / Dimension  4000Vrms	Series	Chassis Mount: World Series?
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 1.8A, Series 900mA  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  25 VA  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  50.80mm L x 49.28mm W  Height - Seated (Max)  Voltage - Isolation  Parallel 14V, Series 28V  Parallel 1.8A, Series 900mA  Pual  Sual  Secondary Winding(s)  Dual  Chassis Mount  Solder, Quick Connect  Size / Dimension  4000Vrms	Туре	Laminated Core
Current - Output (Max)  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  25 VA  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Parallel 1.8A, Series 900mA  Dual  Chassis Mount  Solder, Quick Connect  Solder, Quick Connect  Solder, Quick Connect  4000Vrms	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  25 VA  Mounting Type  Chassis Mount  Termination Style  Solder, Quick Connect  Size / Dimension  Following Type  Solder, Quick Connect  Size / Dimension  Solder, Quick Connect  Solder, Quick Connect  4000Vrms	Voltage - Secondary (Full Load)	Parallel 14V, Series 28V
Secondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension50.80mm L x 49.28mm WHeight - Seated (Max)58.67mmVoltage - Isolation4000Vrms	Current - Output (Max)	Parallel 1.8A, Series 900mA
Center TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension50.80mm L x 49.28mm WHeight - Seated (Max)58.67mmVoltage - Isolation4000Vrms	Primary Winding(s)	Dual
Power - Max  Mounting Type Chassis Mount  Termination Style Solder, Quick Connect Size / Dimension 50.80mm L x 49.28mm W  Height - Seated (Max) 58.67mm  Voltage - Isolation 4000Vrms	Secondary Winding(s)	Dual
Mounting Type Chassis Mount  Termination Style Solder, Quick Connect  Size / Dimension 50.80mm L x 49.28mm W  Height - Seated (Max) 58.67mm  Voltage - Isolation 4000Vrms	Center Tap	No
Termination Style Solder, Quick Connect Size / Dimension 50.80mm L x 49.28mm W Height - Seated (Max) 58.67mm Voltage - Isolation 4000Vrms	Power - Max	25 VA
Size / Dimension50.80mm L x 49.28mm WHeight - Seated (Max)58.67mmVoltage - Isolation4000Vrms	Mounting Type	Chassis Mount
Height - Seated (Max) 58.67mm  Voltage - Isolation 4000Vrms	Termination Style	Solder, Quick Connect
Voltage - Isolation 4000Vrms	Size / Dimension	50.80mm L x 49.28mm W
	Height - Seated (Max)	58.67mm
Weight 1.3 lbs (590.7a)	Voltage - Isolation	4000Vrms
weight 1.5 lbs (569./g)	Weight	1.3 lbs (589.7g)
Report errors?		Report errors?

### **VPS28-900 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **VPS28-900 Payment Methods**



















## **VPS28-900 Shipping Methods**













If you have any question about VPS28-900, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com