

VPS36-3600

VPS36-3600 Information



Part Number	VPS36-3600	
Manufacturer	Triad Magnetics	
Category	Transformers Power Transformers	
Description	XFRMR LAMINATED 130VA CHAS MOUNT	
Package	-	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VPS36-3600 Specifications

ManufacturerTriad MagneticsCategoryTransformersPower TransformersPower TransformersPackage-SeriesChassis Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)DualSecondary Winding(s)DualSecondary Winding(s)DualPower - Max130 VAMounting TypeChassis MountSider, Quick ConnectSider, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)4000Vrms		
CategoryTransformersPower TransformersPackageSeriesChassis Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 18V, Series 3.6APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight1.1bs (1.9kg)	Manufacturer Part Number	VPS36-3600
AngeryPower TransformersPackage-SeriesChassis Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 7.2A, Series 3.6APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountSize / DimensionSolder, Quick ConnectSize / Dimension55.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Manufacturer	Triad Magnetics
Package-SeriesChassis Mount: World Series?TypeLaminated CoreVoltage - PrimaryI15V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36ACurrent - Output (Max)Parallel 7.2A, Series 3.6APrimary Winding(s)DualSecondary Winding(s)DualPower - MaxNoMounting TypeChassis MountTermination StyleSolder, Quick ConnectSte/ Dimension71.37mm Lx 68.33mm WHeight - Seated (Max)SexondWotage - IsolationA000VrmsWeightSult - Sult	Category	Transformers
SeriesChassis Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 7.2A, Series 3.6APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm Lx 68.33mm WHeight - Seated (Max)4000VrmsWoitge I4.1 lbs (1.9kg)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 7.2A, Series 3.6APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm Lx 68.33mm WHeight - Seated (Max)4000VrmsWeight4.1 lbs (1.9kg)	Package	-
Voltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 7.2A, Series 3.6APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChasis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Series	Chassis Mount: World Series?
Voltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 7.2A, Series 3.6APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Туре	Laminated Core
Current - Output (Max)Parallel 7.2A, Series 3.6APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight61.1bs (1.9kg)	Voltage - Secondary (Full Load)	Parallel 18V, Series 36V
Secondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Current - Output (Max)	Parallel 7.2A, Series 3.6A
Center TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Primary Winding(s)	Dual
Power - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Secondary Winding(s)	Dual
Nounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Center Tap	No
Termination StyleSolder, Quick ConnectSize / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Power - Max	130 VA
Size / Dimension71.37mm L x 68.33mm WHeight - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Mounting Type	Chassis Mount
Height - Seated (Max)85.85mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Termination Style	Solder, Quick Connect
Voltage - Isolation4000VrmsWeight4.1 lbs (1.9kg)	Size / Dimension	71.37mm L x 68.33mm W
Weight 4.1 lbs (1.9kg)	Height - Seated (Max)	85.85mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	4.1 lbs (1.9kg)
		Report errors?

VPS36-3600 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about VPS36-3600, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com