

VS-10TQ035STRLHM3

VS-10TQ035STRLHM3 Information

www.heisener.com	VS-10TQ035STRLHM3 Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE RECT 35V 10A D2PAK TO-263-3, D2Pak (2 Leads + Tab), TO-263AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VS-10TQ035STRLHM3 Specifications

Manufacturer Part Number VS-10TQ035STRLHM3 Manufacturer Vishay Semiconductor Diodes Division Category Discrete Semiconductor Products Diodes - Rectifiers - Single Diodes - Rectifiers - Single Package TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) StV Current - Average Rectified Io 10A Voltage - Forward (Vf) (Max) @ If Storte Covery =< 500ns, > 200mA (Io) Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Sund @ 35V Current - Reverse Leakage @ Vr Sund @ 35V Capacitance @ Vr, F 900pF @ 5V, 1MHz Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction 55°C ~ 175°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)35VCurrent - Average Rectified (Io)10AVoltage - Forward (Vf) (Max) @ If570mV @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr2mA @ 35VCurant - Reverse Leakage @ VrSurface MountPackage / CaseSurface MountPackage / CaseD2PAKOperating Temperature - Junction-55°C ~ 175°C	Manufacturer Part Number	VS-10TQ035STRLHM3
Diodes - Rectifiers - Single Package TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 35V Current - Average Rectified (Jo) 10A Voltage - Forward (Vf) (Max) @ If 570mV @ 10A Speed Fast Recovery =< 500ns, > 200mA (Jo) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 2mA @ 35V Current - Reverse Leakage @ Vr 2mA @ 35V Capacitance @ Vr, F 900pF @ 5V, 1MHz Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction -55°C ~ 175°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max) $35V$ Current - Average Rectified (Io) $10A$ Voltage - Forward (Vf) (Max) @ If $570mV @ 10A$ SpeedFast Recovery =< $500ns, > 200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $900pF @ 5V, 1MHz$ Capacitance @ Vr, F $900pF @ 5V, 1MHz$ Mounting TypeSurface MountPackage / Case $TO-263-3, D2Pak (2 Leads + Tab), TO-263AB$ Supplier Device Package $D2PAK$ Operating Temperature - Junction $-55°C ~ 175°C$	Category	Discrete Semiconductor Products
Series-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max) $35V$ Current - Average Rectified (Io) $10A$ Voltage - Forward (Vf) (Max) @ If $570mV @ 10A$ SpeedFast Recovery =< $500ns, > 200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $2mA @ 35V$ Capacitance @ Vr, F $900pF @ 5V, 1MHz$ Mounting TypeSurface MountPackage / Case $TO-263-3, D2Pak (2 Leads + Tab), TO-263AB$ Supplier Device Package $D2PAK$		Diodes - Rectifiers - Single
Diode TypeSchottkyDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)35VCurrent - Average Rectified (Io)10AVoltage - Forward (Vf) (Max) @ If570mV @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr2mA @ 35VCapacitance @ Vr, F900pF @ 5V, 1MHzMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 175°C	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Notage - DC Reverse (Vr) (Max) $35V$ Current - Average Rectified (Io) $10A$ Voltage - Forward (Vf) (Max) @ If $570mV @ 10A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $2mA @ 35V$ Capacitance @ Vr, F $900pF @ 5V$, $1MHz$ Mounting TypeSurface MountPackage / Case $TO-263-3$, $D2Pak$ (2 Leads + Tab), $TO-263AB$ Supplier Device Package $D2PAK$ Operating Temperature - Junction $-55°C ~ 175°C$	Series	-
Current - Average Rectified (Io)10AVoltage - Forward (Vf) (Max) @ If $570mV @ 10A$ SpeedFast Recovery = $500ns, > 200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $2mA @ 35V$ Capacitance @ Vr, F $900pF @ 5V, 1MHz$ Mounting TypeSurface MountPackage / Case $TO-263-3, D2Pak (2 Leads + Tab), TO-263AB$ Supplier Device Package $D2PAK$ Operating Temperature - Junction $-55°C ~ 175°C$	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If $570mV @ 10A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $2mA @ 35V$ Capacitance @ Vr, F $900pF @ 5V$, 1MHzMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction $-55^{\circ}C \sim 175^{\circ}C$	Voltage - DC Reverse (Vr) (Max)	35V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr2mA @ 35VCapacitance @ Vr, F900pF @ 5V, 1MHzMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 175°C	Current - Average Rectified (Io)	10A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr2mA @ 35VCapacitance @ Vr, F900pF @ 5V, 1MHzMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	570mV @ 10A
Current - Reverse Leakage @ Vr2mA @ 35VCapacitance @ Vr, F900pF @ 5V, 1MHzMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 175°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F900pF @ 5V, 1MHzMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 175°C	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 175°C	Current - Reverse Leakage @ Vr	2mA @ 35V
Package / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 175°C	Capacitance @ Vr, F	900pF @ 5V, 1MHz
Supplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 175°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 175^{\circ}C$	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
	Supplier Device Package	D2PAK
Report errors?	Operating Temperature - Junction	-55°C ~ 175°C
Troport directory -		Report errors?

VS-10TQ035STRLHM3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about VS-10TQ035STRLHM3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com