

VS-40CPQ060-N3

VS-40CPQ060-N3 Information

	Part Number	VS-40CPQ060-N3	
	Manufacturer	Vishay Semiconductor Diodes Division	in Notice in
www.helsener.com	Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays	
1	Description	DIODE ARRAY SCHOTTKY 60V TO247AC	
	Package	TO-247-3	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

E-mail: salesdept@heisener.com

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VS-40CPQ060-N3 Specifications

Manufacturer Vishay Semiconductor Diodes Division Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Diodes - Rectifiers - Arrays Package TO-247-3 Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) (per Diode) 40A Voltage - Forward (Vf) (Max) @ If 680mV @ 40A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 1.7mA @ 60V Operating Temperature - Junction -55°C ~ 150°C Mounting Type Through Hole Package / Case TO-247.3		
Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Package TO-247-3 Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) (per Diode) 40A Voltage - Forward (Vf) (Max) @ If 680mV @ 40A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 1.7mA @ 60V Operating Temperature - Junction -55°C ~ 150°C Mounting Type Through Hole Package / Case TO-247-3 Supplier Device Package TO-247AC	Manufacturer Part Number	VS-40CPQ060-N3
Diodes - Rectifiers - ArraysPackageDiodes - Rectifiers - ArraysPackageTO-247-3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io) (per Diode)40AVoltage - Forward (Vf) (Max) @ If680mV @ 40ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr1.7mA @ 60VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Manufacturer	Vishay Semiconductor Diodes Division
Package TO-247-3 Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) (per Diode) 40A Voltage - Forward (Vf) (Max) @ If 680mV @ 40A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (ttr) - Current - Reverse Leakage @ Vr 1.7mA @ 60V Operating Temperature - Junction -55°C ~ 150°C Mounting Type Though Hole Package / Case TO-247.AC	Category	Discrete Semiconductor Products
Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Jo) (per Diode) 40A Voltage - Forward (Vf) (Max) @ If 680mV @ 40A Speed Fast Recovery = < 500ms, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 1.7mA @ 60V Operating Temperature - Junction -St°C ~ 150°C Mounting Type Through Hole Package / Case TO-247AC		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io) (per Diode)40AVoltage - Forward (Vf) (Max) @ If680mV @ 40ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr1.7mA @ 60VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Package	TO-247-3
Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) (per Diode) 40A Voltage - Forward (Vf) (Max) @ If 680mV @ 40A Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 1.7mA @ 60V Operating Temperature - Junction -55°C ~ 150°C Mounting Type Through Hole Package / Case TO-247-3 Supplier Device Package TO-247AC	Series	-
Voltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io) (per Diode)40AVoltage - Forward (Vf) (Max) @ If680mV @ 40ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr1.7mA @ 60VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)40AVoltage - Forward (Vf) (Max) @ If680mV @ 40ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr1.7mA @ 60VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If680mV @ 40ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr1.7mA @ 60VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Voltage - DC Reverse (Vr) (Max)	60V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr1.7mA @ 60VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Current - Average Rectified (Io) (per Diode)	40A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr1.7mA @ 60VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Voltage - Forward (Vf) (Max) @ If	680mV @ 40A
Current - Reverse Leakage @ Vr1.7mA @ 60VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Reverse Recovery Time (trr)	-
Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	Current - Reverse Leakage @ Vr	1.7mA @ 60V
Package / CaseTO-247-3Supplier Device PackageTO-247AC	Operating Temperature - Junction	-55°C ~ 150°C
Supplier Device Package TO-247AC	Mounting Type	Through Hole
	Package / Case	TO-247-3
Report errors?	Supplier Device Package	TO-247AC
		Report errors?

VS-40CPQ060-N3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

VS-40CPQ060-N3 Payment Methods





If you have any question about VS-40CPQ060-N3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com