

VS-80APF10-M3

VS-80APF10-M3 Information

www.helsener.com	Part Number	VS-80APF10-M3	
	Manufacturer	Vishay Semiconductor Diodes Division	
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single	Call Mark
	Description	DIODE FAST REC 80A TO-247	- H . 226 -
M.	Package	TO-247-3	
		For the pricing/inventory/lead time, please contact us	E16.9754
For Reference Only		Website: https://www.heisener.com	Request a Quote

E-mail: salesdept@heisener.com

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VS-80APF10-M3 Specifications

Manufacturer Part NumberVS-80APF10-M3ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SingleDiodes - Rectifiers - SinglePackageTO-247-3Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1000VCurrent - Average Rectified (Io)80AVoltage - Forward (Vf) (Max) @ If1.35V @ 80ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)480nsCurrent - Reverse Leakage @ Vr100µA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247.3Supplier Device PackageTO-247AC	
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-247-3Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1000VCurrent - Average Rectified (Io)80AVoltage - Forward (Vf) (Max) @ If1.35V @ 80ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)480nsCurrent - Reverse Leakage @ Vr1.00µA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Diodes - Rectifiers - SinglePackageTO-247-3Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1000VCurrent - Average Rectified (Io)80AVoltage - Forward (Vf) (Max) @ If1.35V @ 80ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)480nsCurrent - Reverse Leakage @ Vr1.00µA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Package TO-247-3 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) 1000V Current - Average Rectified (Io) 80A Voltage - Forward (Vf) (Max) @ If 1.35V @ 80A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 480ns Current - Reverse Leakage @ Vr 100µA @ 1000V Capacitance @ Vr, F - Mounting Type Through Hole Package / Case TO-247-3 Supplier Device Package TO-247AC	
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1000VCurrent - Average Rectified (Io)80AVoltage - Forward (Vf) (Max) @ If1.35V @ 80ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)480nsCurrent - Reverse Leakage @ Vr100µA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)80AVoltage - Forward (Vf) (Max) @ If1.35V @ 80ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)480nsCurrent - Reverse Leakage @ Vr100µA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Voltage - DC Reverse (Vr) (Max)1000VCurrent - Average Rectified (Io)80AVoltage - Forward (Vf) (Max) @ If1.35V @ 80ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)480nsCurrent - Reverse Leakage @ Vr100µA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Current - Average Rectified (Io)80AVoltage - Forward (Vf) (Max) @ If1.35V @ 80ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)480nsCurrent - Reverse Leakage @ Vr100µA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Voltage - Forward (Vf) (Max) @ If 1.35V @ 80A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 480ns Current - Reverse Leakage @ Vr 100µA @ 1000V Capacitance @ Vr, F - Mounting Type Through Hole Package / Case TO-247-3 Supplier Device Package TO-247AC	
Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) 480ns Current - Reverse Leakage @ Vr 100µA @ 1000V Capacitance @ Vr, F - Mounting Type Through Hole Package / Case TO-247-3 Supplier Device Package TO-247AC	
Reverse Recovery Time (trr)480nsCurrent - Reverse Leakage @ Vr100µA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Current - Reverse Leakage @ Vr100μA @ 1000VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Capacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Mounting TypeThrough HolePackage / CaseTO-247-3Supplier Device PackageTO-247AC	
Package / CaseTO-247-3Supplier Device PackageTO-247AC	
Supplier Device Package TO-247AC	
Operating Temperature - Junction $-40^{\circ}\text{C} \sim 150^{\circ}\text{C}$	
Repo	oort errors?

VS-80APF10-M3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

VS-80APF10-M3 Payment Methods



VS-80APF10-M3 Shipping Methods



If you have any question about VS-80APF10-M3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com