



VS-8EWF04S-M3 Information



For Reference Only

Part Number VS-8EWF04S-M3

Manufacturer Vishay Semiconductor Diodes Division

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE GEN PURP 400V 8A TO252AA **Package** TO-252-3, DPak (2 Leads + Tab), SC-63

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VS-8EWF04S-M3 Specifications

Manufacturer Part NumberVS-8EWF04S-M3ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.2V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)55nsCurrent - Reverse Leakage @ Vr100µA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)Operating Temperature - Junction-40°C ~ 150°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.2V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)55nsCurrent - Reverse Leakage @ Vr100μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)Operating Temperature - Junction-40°C ~ 150°C	Manufacturer Part Number	VS-8EWF04S-M3
Diodes - Rectifiers - Single TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 8A Voltage - Forward (Vf) (Max) @ If 1.2V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 55ns Current - Reverse Leakage @ Vr 100µA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction	Manufacturer	Vishay Semiconductor Diodes Division
Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) 400V Current - Average Rectified (Io) 8A Voltage - Forward (Vf) (Max) @ If 1.2V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 55ns Current - Reverse Leakage @ Vr 100μA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction -40°C ~ 150°C	Category	Discrete Semiconductor Products
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.2V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)55nsCurrent - Reverse Leakage @ Vr100μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)Operating Temperature - Junction-40°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.2V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)55nsCurrent - Reverse Leakage @ Vr100μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)Operating Temperature - Junction-40°C ~ 150°C	Package	TO-252-3, DPak (2 Leads + Tab), SC-63
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 8A Voltage - Forward (Vf) (Max) @ If 1.2V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 55ns Current - Reverse Leakage @ Vr 100μA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction	Series	-
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.2V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 55ns Current - Reverse Leakage @ Vr 100µA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 55ns Current - Reverse Leakage @ Vr 100μA @ 400V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction -40°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	400V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)55nsCurrent - Reverse Leakage @ Vr100μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)Operating Temperature - Junction-40°C ~ 150°C	Current - Average Rectified (Io)	8A
Reverse Recovery Time (trr)55nsCurrent - Reverse Leakage @ Vr100μA @ 400VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)Operating Temperature - Junction-40°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.2V @ 8A
Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction -40°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction -40°C ~ 150°C	Reverse Recovery Time (trr)	55ns
Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction -40°C ~ 150°C	Current - Reverse Leakage @ Vr	100μA @ 400V
Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction -40°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device Package D-PAK (TO-252AA) Operating Temperature - Junction $-40^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Mounting Type	Surface Mount
Operating Temperature - Junction -40°C ~ 150°C	Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63
	Supplier Device Package	D-PAK (TO-252AA)
Report errors?	Operating Temperature - Junction	-40°C ~ 150°C
		Report errors?

VS-8EWF04S-M3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VS-8EWF04S-M3 Payment Methods



















VS-8EWF04S-M3 Shipping Methods













If you have any question about VS-8EWF04S-M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com