

VS-8EWF12STRRPBF

VS-8EWF12STRRPBF Information



For Reference Only

Part Number VS-8EWF12STRRPBF

Manufacturer Vishay Semiconductor Diodes Division

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

DescriptionDIODE FAST RECOVERY 8A DPAK**Package**TO-252-3, DPak (2 Leads + Tab), SC-63

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VS-8EWF12STRRPBF Specifications

Manufacturer Part NumberVS-8EWF12STRRPBFManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.3V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)270nsCurrent - Reverse Leakage @ Vr100μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)Operating Temperature - Junction-40°C ~ 150°C		
Category Discrete Semiconductor Products Diodes - Rectifiers - Single Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) 1200V Current - Average Rectified (Io) 8A Voltage - Forward (Vf) (Max) @ If 1.3V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 270ns Current - Reverse Leakage @ Vr 100µA @ 1200V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA)	Manufacturer Part Number	VS-8EWF12STRRPBF
Diodes - Rectifiers - Single Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) 1200V Current - Average Rectified (Io) 8A Voltage - Forward (Vf) (Max) @ If 1.3V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 270ns Current - Reverse Leakage @ Vr 100μA @ 1200V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA)	Manufacturer	Vishay Semiconductor Diodes Division
Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 8A Voltage - Forward (Vf) (Max) @ If 1.3V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 270ns Current - Reverse Leakage @ Vr 100μA @ 1200V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package	Category	Discrete Semiconductor Products
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.3V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)270nsCurrent - Reverse Leakage @ Vr100μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.3V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)270nsCurrent - Reverse Leakage @ Vr100μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)	Package	TO-252-3, DPak (2 Leads + Tab), SC-63
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 8A Voltage - Forward (Vf) (Max) @ If 1.3V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 270ns Current - Reverse Leakage @ Vr 100µA @ 1200V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA)	Series	-
Current - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.3V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)270nsCurrent - Reverse Leakage @ Vr100μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 270ns Current - Reverse Leakage @ Vr 100μA @ 1200V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA)	Voltage - DC Reverse (Vr) (Max)	1200V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)270nsCurrent - Reverse Leakage @ Vr100μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)	Current - Average Rectified (Io)	8A
Reverse Recovery Time (trr)270nsCurrent - Reverse Leakage @ Vr100μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageD-PAK (TO-252AA)	Voltage - Forward (Vf) (Max) @ If	1.3V @ 8A
Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA)	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA)	Reverse Recovery Time (trr)	270ns
Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA)	Current - Reverse Leakage @ Vr	100μA @ 1200V
Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package D-PAK (TO-252AA)	Capacitance @ Vr, F	-
Supplier Device Package D-PAK (TO-252AA)	Mounting Type	Surface Mount
	Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63
Operating Temperature - Junction $-40^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Supplier Device Package	D-PAK (TO-252AA)
• • •	Operating Temperature - Junction	-40°C ~ 150°C
Report errors?		Report errors?

VS-8EWF12STRRPBF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VS-8EWF12STRRPBF Payment Methods





















VS-8EWF12STRRPBF Shipping Methods













If you have any question about VS-8EWF12STRRPBF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com