

VS-HFA25TB60STRLP

VS-HFA25TB60STRLP Information



For Reference Only

Part Number VS-HFA25TB60STRLP

Manufacturer Vishay Semiconductor Diodes Division

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE GEN PURP 600V 25A D2PAK

Package TO-263-3, D2Pak (2 Leads + Tab), TO-263AB

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VS-HFA25TB60STRLP Specifications

Manufacturer Part NumberVS-HFA25TB60STRLPManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)25A (DC)Voltage - Forward (Vf) (Max) @ If1.7V @ 25ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)25A (DC)Voltage - Forward (Vf) (Max) @ If1.7V @ 25ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	VS-HFA25TB60STRLP
Diodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)25A (DC)Voltage - Forward (Vf) (Max) @ If1.7V @ 25ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)25A (DC)Voltage - Forward (Vf) (Max) @ If1.7V @ 25ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
SeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)25A (DC)Voltage - Forward (Vf) (Max) @ If1.7V @ 25ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)25A (DC)Voltage - Forward (Vf) (Max) @ If1.7V @ 25ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.7V @ 25A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 75ns Current - Reverse Leakage @ Vr 20μA @ 600V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction 600V 25A (DC) 1.7V @ 25A 500ns, > 200mA (Io) 75ns 20μA @ 600V 20	Series	HEXFRED?
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.7V @ 25A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 75ns Current - Reverse Leakage @ Vr 20µA @ 600V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package Operating Temperature - Junction 25A (DC) 1.7V @ 25A 1.7V @ 25A Supplier Device Ackage Fast Recovery =< 500ns, > 200mA (Io) 75ns 20µA @ 600V 20µA @ 600V -55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.7V @ 25ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	600V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)75nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	25A (DC)
Reverse Recovery Time (trr) 75ns	Voltage - Forward (Vf) (Max) @ If	1.7V @ 25A
Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction 20μA @ 600V - TO-263-3, D2Pak (2 Leads + Tab), TO-263AB D2PAK	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction -55°C ~ 150°C	Reverse Recovery Time (trr)	75ns
Mounting Type Surface Mount TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction -55°C ~ 150°C	Current - Reverse Leakage @ Vr	20μA @ 600V
Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction -55°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device Package D2PAK Operating Temperature - Junction -55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 150°C	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
	Supplier Device Package	D2PAK
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

VS-HFA25TB60STRLP Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VS-HFA25TB60STRLP Payment Methods



















VS-HFA25TB60STRLP Shipping Methods













If you have any question about VS-HFA25TB60STRLP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com