

# **VS-MUR2020CT-N3**

## **VS-MUR2020CT-N3 Information**

www.itelsede.com	Part Number	VS-MUR2020CT-N3	
	Manufacturer	Vishay Semiconductor Diodes Division	ETL#286
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays	
	Description	DIODE STANDARD 200V 10A TO220AB	
	Package	TO-220-3	一番恋恋的
		For the pricing/inventory/lead time, please contact	E126-06-0
or Reference Only		us Website: https://www.heisener.com	Degraat o Or

E-mail: salesdept@heisener.com

For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

# VS-MUR2020CT-N3 Specifications

ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysDiodes - Rectifiers - ArraysPackageTO-220-3SeriesFRED Pt?Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery = 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15 $\mu$ A @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageTO-220-3SeriesFRED Pt?Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220.3Supplier Device PackageTO-220AB	Manufacturer Part Number	VS-MUR2020CT-N3
Diodes - Rectifiers - ArraysPackageTO-220-3SeriesFRED Pt?Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220AB	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-220-3SeriesFRED Pt?Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (ttr)35nsCurrent - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Category	Discrete Semiconductor Products
SeriesFRED Pt?Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220AB		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Package	TO-220-3
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Series	FRED Pt?
Voltage - DC Reverse (Vr) (Max)200VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15μA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If850mV @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15μA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Voltage - DC Reverse (Vr) (Max)	200V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Current - Average Rectified (Io) (per Diode)	10A
Reverse Recovery Time (trr)35nsCurrent - Reverse Leakage @ Vr15μA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Voltage - Forward (Vf) (Max) @ If	850mV @ 8A
Current - Reverse Leakage @ Vr15µA @ 200VOperating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-65°C ~ 175°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Reverse Recovery Time (trr)	35ns
Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Current - Reverse Leakage @ Vr	15μA @ 200V
Package / CaseTO-220-3Supplier Device PackageTO-220AB	Operating Temperature - Junction	-65°C ~ 175°C
Supplier Device Package TO-220AB	Mounting Type	Through Hole
	Package / Case	TO-220-3
Report errors?	Supplier Device Package	TO-220AB
		Report errors?

#### VS-MUR2020CT-N3 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## VS-MUR2020CT-N3 Payment Methods





If you have any question about VS-MUR2020CT-N3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com