

VS150B3 Information

Heisener.com

VS150B3 Part Number

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 3.3V 150W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VS150B3 Specifications

Manufacturer Part Number VS150B3 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VSB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 150W Applications ITE (commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VSB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Manufacturer Part Number	VS150B3
Package - Series VSB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series VSB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series VSB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Series	VSB
Voltage - Input 85 ~ 132 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature Features Adjustable Output, DC Input Capable Mounting Type Size / Dimension 3.3V 3.3V 3.3V 3.3V 3.3V Chassis Mount 5.3V Chassis Mount 5.3V Chassis Mount 5.3V A.3 A.3 A.3 A.3 A.3 A.3 A.3	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency Operating Temperature Features Adjustable Output, DC Input Capable Mounting Type Size / Dimension - Voltage - Output 4 - Current - Output (Max) - Size / Dimension - Current - Output (Max) - Current -	Voltage - Input	85 ~ 132 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature Features Adjustable Output, DC Input Capable Mounting Type Size / Dimension - Output (Max) - Commercial (Ma	Voltage - Output 1	3.3V
Voltage - Output 4 Current - Output (Max) 30A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 150W 2kV (2000V) 72% Climpit Capable Chassis Mount 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Current - Output (Max)	30A
Voltage - Isolation 2kV (2000V) Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Power (Watts)	150W
Efficiency 72% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Voltage - Isolation	2kV (2000V)
Features Adjustable Output, DC Input Capable Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Efficiency	72%
Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Operating Temperature	-10°C ~ 70°C (With Derating)
Size / Dimension 8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)	Features	Adjustable Output, DC Input Capable
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	8.74" L x 2.95" W x 1.42" H (222.0mm x 75.0mm x 36.0mm)
		Report errors?

VS150B3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VS150B3 Payment Methods





















VS150B3 Shipping Methods













If you have any question about VS150B3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com