

VS30C24 Information

Part Number VS30C24

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 30W

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VS30C24 Specifications

Manufacturer Part Number VS30C24 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VSC Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VSC Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Manufacturer Part Number	VS30C24
Package - Series VSC Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Manufacturer	TDK-Lambda Americas Inc.
Package - Series VSC Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Category	Power Supplies - External/Internal (Off-Board)
Series VSC Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Series	VSC
Voltage - Input 85 ~ 132 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Type	Open Frame
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Number of Outputs	1
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Voltage - Input	85 ~ 132 VAC
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Voltage - Output 3	-
Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 2kV (2000V) Efficiency 82%	Current - Output (Max)	1.3A
Voltage - Isolation 2kV (2000V) Efficiency 82%	Power (Watts)	30W
Efficiency 82%	Applications	ITE (Commercial)
·	Voltage - Isolation	2kV (2000V)
	Efficiency	82%
Operating Temperature $-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Operating Temperature	-10° C ~ 70° C (With Derating)
Features Adjustable Output, DC Input Capable	Features	Adjustable Output, DC Input Capable
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Size / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Size / Dimension	5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)
Report error		Report errors?

VS30C24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VS30C24 Payment Methods



















VS30C24 Shipping Methods













If you have any question about VS30C24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com