

## VS30C36

#### VS30C36 Information

	Part Number Manufacturer Category Description Package	VS30C36 TDK-Lambda Americas Inc. Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 36V 30W - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### VS30C36 Specifications

ManufacturerTDK-Lambda Americas Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesVSCSpeisVSCNumber of Outputs1Voltage - Input85 ~ 132 VACVoltage - Output 165 ~ 132 VACVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4900mAVoltage - Output 430WApplicationsITE (Commercial)Voltage - Isolation2kV (2000V)Efficiency80%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChasis Mount			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesVSCTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 132 VACVoltage - Output 164Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4900mACurrent - Output (Max)900mAApplicationsTE (Commercial)Voltage - Isolation2kV (200V)Efficiency80%Operating Fremperature-10°C ~ 0°C (With Derating)FeaturesAdjustable Output, DC Input CapableKunuting Type5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Manufacturer Part Number	V\$30C36	
AC DC Converters   Package -   Series VSC   Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 132 VAC   Voltage - Output 1 36V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Solation JOW   Power (Watts) 30W   Applications ITE (Commercial)   Voltage - Isolation 2kV (200V)   Efficiency 80%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable   Mounting Type Chassis Mount   Size / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package-SeriesVSCTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 132 VACVoltage - Output 136VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4900mACurrent - Output (Max)900mAPower (Watts)30WVoltage - Isolation1FE (Commercial)Voltage - Isolation80%Operating Temperature-0°C ~ 0°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting Type5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series VSC   Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 132 VAC   Voltage - Output 1 36V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 900mA   Applications ITE (Commercial)   Voltage - Isolation 2kV (2000V)   Efficiency 80%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable   Mounting Type Chasis Mount   Size / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)		AC DC Converters	
Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 132 VAC   Voltage - Output 1 36V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 5 900mA   Power (Watts) 30W   Applications ITE (Commercial)   Voltage - Isolation 2kV (2000V)   Efficiency 80%   Operating Temperature -10°C ~ 0°C (With Derating)   Features Adjustable Output, DC Input Capable   Mounting Type Chassis Mount   Size / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Package	-	
Number of Outputs I   Voltage - Input 85 ~ 132 VAC   Voltage - Output 1 36V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 900mA   Power (Watts) 30W   Applications ITE (Commercial)   Voltage - Isolation 2kV (200V)   Efficiency 80%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable   Mounting Type Chassis Mount   Size / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Series	VSC	
Voltage - Input 85 ~ 132 VAC   Voltage - Output 1 36V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 4 -   Current - Output (Max) 900mA   Power (Watts) 30W   Applications ITE (Commercial)   Voltage - Isolation 2kV (2000V)   Efficiency 80%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable   Mounting Type Chassis Mount   Size / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Туре	Open Frame	
Voltage - Output 1 36V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 900mA   Power (Watts) 30W   Applications TTE (Commercial)   Voltage - Isolation 2kV (2000V)   Efficiency 80%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable   Mounting Type Chassis Mount   Size / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Number of Outputs	1	
Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 900mA   Power (Watts) 30W   Applications ITE (Commercial)   Voltage - Isolation 2kV (2000V)   Efficiency 80%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable   Mounting Type 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Voltage - Input	85 ~ 132 VAC	
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)900mAPower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation2kV (2000V)Efficiency80%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Voltage - Output 1	36V	
Voltage - Output 4-Current - Output (Max)900mAPower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation2kV (2000V)Efficiency80%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Voltage - Output 2	-	
Current - Output (Max)900mAPower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation2kV (2000V)Efficiency80%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Voltage - Output 3	-	
Power (Watts)30WApplicationsITE (Commercial)Voltage - Isolation2kV (2000V)Efficiency80%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Voltage - Output 4	-	
ApplicationsITE (Commercial)Voltage - Isolation2kV (2000V)Efficiency80%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Current - Output (Max)	900mA	
InInVoltage - Isolation2kV (2000V)Efficiency80%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Power (Watts)	30W	
Efficiency80%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Applications	ITE (Commercial)	
Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Voltage - Isolation	2kV (2000V)	
FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Efficiency	80%	
Mounting TypeChassis MountSize / Dimension5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Operating Temperature	$-10^{\circ}$ C ~ $70^{\circ}$ C (With Derating)	
Size / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	Features	Adjustable Output, DC Input Capable	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	e / Dimension 5.22" L x 1.97" W x 0.98" H (132.5mm x 50.0mm x 25.0mm)	
		Report	errors?

#### VS30C36 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about VS30C36, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com