

### **VS50B3 Information**

Heisener.com

Part Number VS50B3

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 3.3V 50W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VS50B3 Specifications**

Manufacturer Part Number         V\$50B3           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         VSB           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         73%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)   Report errors?	-	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         VSB           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         73%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Manufacturer Part Number	VS50B3
Package         -           Series         VSB           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         73%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package         -           Series         VSB           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         73%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         VSB           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         73%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         73%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Package	-
Number of Outputs       1         Voltage - Input       85 ~ 132 VAC         Voltage - Output 1       3.3V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       10A         Power (Watts)       50W         Applications       ITE (Commercial)         Voltage - Isolation       2kV (2000V)         Efficiency       73%         Operating Temperature       -10°C ~ 70°C (With Derating)         Features       Adjustable Output, DC Input Capable         Mounting Type       Chassis Mount         Size / Dimension       7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Series	VSB
Voltage - Input         85 ~ 132 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         2kV (2000V)           Efficiency         73%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Type	Enclosed
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2kV (2000V)  Efficiency  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Mounting Type  Chassis Mount  Size / Dimension  3.3V  3.3V  3.3V  3.3V  3.3V  3.3V  Chassis Mount  10A  -10A  -10A	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  Voltage - Isolation  Voltage - Isolation  Efficiency  Operating Temperature  Features  Mounting Type  Size / Dimension  - Current - Output (Max)  10A  - Current - Output (Max)  10A  Fower (Watts)  50W  Advantage  Fower (Watts)  50W  Available Output (Max)  Fower (Watts)  Fower (	Voltage - Input	85 ~ 132 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2kV (2000V)  Efficiency  73%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable  Mounting Type  Chassis Mount  Size / Dimension  - Output 3  - Output (Max)  - Output (	Voltage - Output 1	3.3V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2kV (2000V)  Efficiency  73%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable  Mounting Type  Chassis Mount  Size / Dimension  -10°C ~ 7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  50W  Applications  ITE (Commercial)  Voltage - Isolation  2kV (2000V)  Efficiency  73%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable  Mounting Type  Chassis Mount  Size / Dimension  10A  10A  10A  10A  10B  10B  10B  10B	Voltage - Output 3	-
Power (Watts) 50W  Applications ITE (Commercial)  Voltage - Isolation 2kV (2000V)  Efficiency 73%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $2kV$ (2000V)Efficiency $73\%$ Operating Temperature $-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, DC Input CapableMounting TypeChassis MountSize / Dimension $7.68$ " L x $1.97$ " W x $0.98$ " H ( $195.0$ mm x $50.0$ mm x $25.0$ mm)	Current - Output (Max)	10A
Voltage - Isolation 2kV (2000V)  Efficiency 73%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Power (Watts)	50W
Efficiency 73%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Voltage - Isolation	2kV (2000V)
Features Adjustable Output, DC Input Capable  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Efficiency	73%
Mounting Type Chassis Mount Size / Dimension 7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)	Features	Adjustable Output, DC Input Capable
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.68" L x 1.97" W x 0.98" H (195.0mm x 50.0mm x 25.0mm)
		Report errors?

### **VS50B3 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **VS50B3 Payment Methods**



















# **VS50B3 Shipping Methods**













If you have any question about VS50B3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com