

VSK-S2-12U Information



For Reference Only

Part Number VSK-S2-12U Manufacturer CUI Inc.

Category Power Supplies - Board Mount

AC DC Converters

Description POWER SUPPLY SWITCHING 12V 2W

Package 4-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VSK-S2-12U Specifications

Manufacturer CUI Inc. Category Power Supplies - Board Mount AC DC Converters Package 4-DIP Module Series VSK-S2 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 305 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module		
Category Power Supplies - Board Mount AC DC Converters Package 4-DIP Module Series VSK-S2 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 305 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Manufacturer Part Number	VSK-S2-12U
AC DC Converters Package 4-DIP Module Series VSK-S2 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 305 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Manufacturer	CUI Inc.
Package 4-DIP Module Series VSK-S2 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 305 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Category	Power Supplies - Board Mount
Series VSK-S2 Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 305 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 305 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Package	4-DIP Module
Number of Outputs 1 Voltage - Input 85 ~ 305 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Series	VSK-S2
Voltage - Input 85 ~ 305 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Туре	Enclosed
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Number of Outputs	1
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Voltage - Input	85 ~ 305 VAC
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 167mA Power (Watts) 2W Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension -167mA -2W Current - Output (Max) 1TE (Commercial) OCP, SCP OCP, SCP -25°C ~ 70°C (With Derating) Through Hole 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 2W THE (Commercial) OCP, SCP -25°C ~ 70°C (With Derating) Through Hole 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Current - Output (Max)	167mA
Features OCP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Power (Watts)	2W
Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Applications	ITE (Commercial)
Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Features	OCP, SCP
Mounting Type Through Hole Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Operating Temperature	-25°C ~ 70 °C (With Derating)
Package / Case 4-DIP Module Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Efficiency	76%
Size / Dimension 1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)	Mounting Type	Through Hole
	Package / Case	4-DIP Module
Report errors?	Size / Dimension	1.33" L x 0.87" W x 0.71" H (33.7mm x 22.2mm x 18.0mm)
		Report errors?

VSK-S2-12U Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VSK-S2-12U Payment Methods



















VSK-S2-12U Shipping Methods













If you have any question about VSK-S2-12U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com