

## **VSK-S5-15UA Information**



For Reference Only

Part Number VSK-S5-15UA

Manufacturer CUI Inc.

**Category** Power Supplies - Board Mount

AC DC Converters

**Description** CONV AC/DC 5W 15V 0.33A PCB

Package 4-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VSK-S5-15UA Specifications**

Manufacturer Part Number         VSK-S5-15UA           Manufacturer         CUI Inc.           Category         Power Supplies - Board Mount           AC DC Converters           Package         4-DIP Module           Series         VSK-S5           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         330mA           Power (Watts)         5W           Applications         ITE (Commercial)           Features         OTP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         76%           Mounting Type         Through Hole           Package / Case         4-DIP Module           Size / Dimension         2.00" L x 1.00" W x 0.62" H (50.8mm x 25.4mm x 15.7mm)		
Category         Power Supplies - Board Mount           AC DC Converters           Package         4-DIP Module           Series         VSK-S5           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         330mA           Power (Watts)         5W           Applications         ITE (Commercial)           Features         OTP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         76%           Mounting Type         Through Hole           Package / Case         4-DIP Module	Manufacturer Part Number	VSK-S5-15UA
Package         4-DIP Module           Series         VSK-S5           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         330mA           Power (Watts)         5W           Applications         ITE (Commercial)           Features         OTP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         76%           Mounting Type         Through Hole           Package / Case         4-DIP Module	Manufacturer	CUI Inc.
Package         4-DIP Module           Series         VSK-S5           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         330mA           Power (Watts)         5W           Applications         ITE (Commercial)           Features         OTP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         76%           Mounting Type         Through Hole           Package / Case         4-DIP Module	Category	Power Supplies - Board Mount
Series         VSK-S5           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         330mA           Power (Watts)         5W           Applications         ITE (Commercial)           Features         OTP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         76%           Mounting Type         Through Hole           Package / Case         4-DIP Module		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         330mA           Power (Watts)         5W           Applications         ITE (Commercial)           Features         OTP, OVP, SCP           Operating Temperature         -25°C ~ 70°C (With Derating)           Efficiency         76%           Mounting Type         Through Hole           Package / Case         4-DIP Module	Package	4-DIP Module
Number of Outputs       1         Voltage - Input       85 ~ 264 VAC         Voltage - Output 1       15V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       330mA         Power (Watts)       5W         Applications       ITE (Commercial)         Features       OTP, OVP, SCP         Operating Temperature       -25°C ~ 70°C (With Derating)         Efficiency       76%         Mounting Type       Through Hole         Package / Case       4-DIP Module	Series	VSK-S5
Voltage - Input  Voltage - Output 1  15V  Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  Features  OTP, OVP, SCP  Operating Temperature  Efficiency  Mounting Type  Package / Case  85 ~ 264 VAC  15V	Type	Enclosed
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  Current - Output (Max)  Applications  Features  Operating Temperature  Efficiency  Mounting Type  Package / Case  15V	Number of Outputs	1
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  Features  OTP, OVP, SCP  Operating Temperature  OTP, OVP, SCP  Mounting Type  Package / Case	Voltage - Input	85 ~ 264 VAC
Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OTP, OVP, SCP Operating Temperature Efficiency Mounting Type Package / Case	Voltage - Output 1	15V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Features  OTP, OVP, SCP  Operating Temperature  -25°C ~ 70°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  4-DIP Module	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Features  OTP, OVP, SCP  Operating Temperature  -25°C ~ 70°C (With Derating)  Efficiency  Mounting Type  Through Hole  Package / Case  4-DIP Module	Voltage - Output 3	-
Power (Watts) 5W  Applications ITE (Commercial)  Features OTP, OVP, SCP  Operating Temperature -25°C ~ 70°C (With Derating)  Efficiency 76%  Mounting Type Through Hole  Package / Case 4-DIP Module	Voltage - Output 4	-
Applications ITE (Commercial)  Features OTP, OVP, SCP  Operating Temperature -25°C ~ 70°C (With Derating)  Efficiency 76%  Mounting Type Through Hole  Package / Case 4-DIP Module	Current - Output (Max)	330mA
Features OTP, OVP, SCP Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)  Efficiency 76% Mounting Type Through Hole Package / Case 4-DIP Module	Power (Watts)	5W
Operating Temperature -25°C ~ 70°C (With Derating)  Efficiency 76%  Mounting Type Through Hole  Package / Case 4-DIP Module	Applications	ITE (Commercial)
Efficiency 76%  Mounting Type Through Hole  Package / Case 4-DIP Module	Features	OTP, OVP, SCP
Mounting Type Through Hole Package / Case 4-DIP Module	Operating Temperature	-25°C ~ 70°C (With Derating)
Package / Case 4-DIP Module	Efficiency	76%
	Mounting Type	Through Hole
Size / Dimension 2.00" L x 1.00" W x 0.62" H (50.8mm x 25.4mm x 15.7mm)	Package / Case	4-DIP Module
	Size / Dimension	2.00" L x 1.00" W x 0.62" H (50.8mm x 25.4mm x 15.7mm)
Report error		Report errors?

#### **VSK-S5-15UA Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **VSK-S5-15UA Payment Methods**





















## **VSK-S5-15UA Shipping Methods**













If you have any question about VSK-S5-15UA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com