

VSUU-150-48 Information



For Reference Only

Part Number VSUU-150-48 Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 150W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VSUU-150-48 Specifications

Manufacturer Part Number VSUU-150-48 Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VSUU-150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VSUU-150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output (Max) 3.13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Manufacturer Part Number	VSUU-150-48	
Package - Series VSUU-150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Manufacturer	CUI Inc.	
Package - Series VSUU-150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series VSUU-150 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)		AC DC Converters	
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Package	-	
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Series	VSUU-150	
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Type	Open Frame	
Voltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)3.13APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation4.242kV (4242V)Efficiency80%Operating Temperature0°C ~ 70°C (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature Features Universal Input Mounting Type Size / Dimension	Voltage - Input	90 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension Current - Output (Max)	Voltage - Output 1	48V	
Voltage - Output 4 Current - Output (Max) 3.13A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Voltage - Output 2	-	
Current - Output (Max) 3.13A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 3.13A 3.13A 150W 17E (Commercial) 4.242kV (4242V) 80% 80% Operating Temperature 0°C ~ 70°C (With Derating) Universal Input 17E (Commercial) 4.242kV (4242V) 80% 18E (Size / Dimension) 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 150W 4.242kV (4242V) 80% Commercial) 4.242kV (4242V) 80% Features Universal Input Chassis Mount 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Voltage - Output 4	-	
ApplicationsITE (Commercial)Voltage - Isolation $4.242kV$ ($4242V$)Efficiency 80% Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $5.00^{\circ}L \times 3.21^{\circ}W \times 1.62^{\circ}H$ ($127.0mm \times 81.6mm \times 41.2mm$)	Current - Output (Max)	3.13A	
Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Power (Watts)	150W	
Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $5.00^{\circ}\text{L x } 3.21^{\circ}\text{W x } 1.62^{\circ}\text{H } (127.0\text{mm x } 81.6\text{mm x } 41.2\text{mm})$	Applications	ITE (Commercial)	
Operating Temperature0°C ~ 70°C (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Voltage - Isolation	4.242kV (4242V)	
Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Efficiency	80%	
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	
Size / Dimension 5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	Features	Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.21" W x 1.62" H (127.0mm x 81.6mm x 41.2mm)	
		Report errors	?

VSUU-150-48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VSUU-150-48 Payment Methods



















VSUU-150-48 Shipping Methods













If you have any question about VSUU-150-48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com