

# WAU160-750 Information



For Reference Only

Part Number WAU160-750 Manufacturer Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

**Description** AC/AC WALL MNT ADAPTER 16V 750MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **WAU160-750 Specifications**

Manufacturer Part NumberWAU160-750ManufacturerTriad MagneticsCategoryPower Supplies - External/Internal (Off-Board)Package-SeriesWAU160Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output16VACCurrent - Output (Max)750mAPower (Watts)12WNo Load Power Consumption210mW (Max)ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-10°C ~ 50°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)ApprovalscULus	•	
Category         Power Supplies - External/Internal (Off-Board)           AC AC Wall Adapters           Package         -           Series         WAU160           Region Utilized         North America           Form         Wall Mount (Class II)           Input Type         Fixed Blade           Voltage - Input         120 VAC           Voltage - Output         16 VAC           Current - Output (Max)         750mA           Power (Watts)         12W           No Load Power Consumption         210mW (Max)           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         -10°C ~ 50°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm           Size / Dimension         1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)           Approvals         cULus	Manufacturer Part Number	WAU160-750
AC AC Wall Adapters  Package Series WAU160 Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 750mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals	Manufacturer	Triad Magnetics
Package - Series WAU160  Region Utilized North America Form Wall Mount (Class II)  Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 16VAC  Current - Output (Max) 750mA  Power (Watts) 12W  No Load Power Consumption 210mW (Max)  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature -10°C ~ 50°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals	Category	Power Supplies - External/Internal (Off-Board)
SeriesWAU160Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output16VACCurrent - Output (Max)750mAPower (Watts)12WNo Load Power Consumption210mW (Max)ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-10°C ~ 50°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)ApprovalscULus		AC AC Wall Adapters
Region Utilized  Form  Wall Mount (Class II)  Input Type  Fixed Blade  Voltage - Input  120VAC  Voltage - Output  16VAC  Current - Output (Max)  Power (Watts)  No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  -10°C ~ 50°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals	Package	-
Form Wall Mount (Class II)  Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 16VAC  Current - Output (Max) 750mA  Power (Watts) 12W  No Load Power Consumption 210mW (Max)  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature -10°C ~ 50°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals	Series	WAU160
Input Type  Fixed Blade  Voltage - Input  120VAC  Voltage - Output  16VAC  Current - Output (Max)  Power (Watts)  No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Operating Temperature  -10°C ~ 50°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  Approvals  Fixed Blade  120VAC  16VAC  16VAC  750mA  12W  No Load Power Consumption  210mW (Max)  Level VI  Operating Temperature  -10°C ~ 50°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  cULus	Region Utilized	North America
Voltage - Input         120VAC           Voltage - Output         16VAC           Current - Output (Max)         750mA           Power (Watts)         12W           No Load Power Consumption         210mW (Max)           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         -10°C ~ 50°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm           Size / Dimension         1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)           Approvals         cULus	Form	Wall Mount (Class II)
Voltage - Output (Max)  Current - Output (Max)  Power (Watts)  No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals  cULus	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  12W  No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Current - Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  CULus	Voltage - Input	120VAC
Power (Watts)  12W  No Load Power Consumption  210mW (Max)  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  -10°C ~ 50°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals  cULus	Voltage - Output	16VAC
No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  -10°C ~ 50°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  cULus	Current - Output (Max)	750mA
Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature -10°C ~ 50°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals cULus	Power (Watts)	12W
Efficiency Level VI  Operating Temperature $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals cULus	No Load Power Consumption	210mW (Max)
Operating Temperature $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Applications	ITE (Commercial)
Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals  cULus	Efficiency	Level VI
Size / Dimension         1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)           Approvals         cULus	Operating Temperature	-10°C ~ 50°C
Approvals cULus	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm
	Size / Dimension	1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)
Report errors?	Approvals	cULus
		Report errors?

#### WAU160-750 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **WAU160-750 Payment Methods**



















### **WAU160-750 Shipping Methods**













If you have any question about WAU160-750, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com