



WAU200-600T Information



For Reference Only

Part Number WAU200-600T Manufacturer Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MNT ADAPTER 20V 600MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WAU200-600T Specifications

Manufacturer WAU200-600T Manufacturer Triad Magnetics Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series WAU200 Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 20VAC Current - Output (Max) 600mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus			
CategoryPower Supplies - External/Internal (Off-Board)AC AC Wall AdaptersPackage-SeriesWAU200Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output20VACCurrent - Output (Max)600mAPower (Watts)12WNo Load Power Consumption210mW (Max)ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-10°C ~ 50°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)ApprovalscULus	Manufacturer Part Number	WAU200-600T	
AC AC Wall Adapters Package - Series WAU200 Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 20VAC Current - Output (Max) 600mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals	Manufacturer	Triad Magnetics	
Package - Series WAU200 Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 20VAC Current - Output (Max) 600mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals	Category	Power Supplies - External/Internal (Off-Board)	
SeriesWAU200Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output20VACCurrent - Output (Max)600mAPower (Watts)12WNo Load Power Consumption210mW (Max)ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-10°C ~ 50°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)ApprovalscULus		AC AC Wall Adapters	
Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 20VAC Current - Output (Max) 600mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals	Package	-	
Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 20VAC Current - Output (Max) 600mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Series	WAU200	
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 20VAC Current - Output (Max) 600mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Region Utilized	North America	
Voltage - Input 120VAC Voltage - Output 20VAC Current - Output (Max) 600mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals	Form	Wall Mount (Class II)	
Voltage - Output (Max) 600mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Input Type	Fixed Blade	
Current - Output (Max) Power (Watts) 12W No Load Power Consumption Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Voltage - Input	120VAC	
Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Voltage - Output	20VAC	
No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Current - Output (Max)	600mA	
Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Power (Watts)	12W	
Efficiency Level VI Operating Temperature $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	No Load Power Consumption	210mW (Max)	
Operating Temperature $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Applications	ITE (Commercial)	
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) cULus	Efficiency	Level VI	
Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Operating Temperature	-10°C ~ 50°C	
Approvals cULus	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm	
	Size / Dimension	1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)	
Report errors?	Approvals	cULus	
			Report errors?

WAU200-600T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WAU200-600T Payment Methods





















WAU200-600T Shipping Methods













If you have any question about WAU200-600T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com