

WAU240-500T Information



For Reference Only

Part Number WAU240-500T **Manufacturer** Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MNT ADAPTER 24V 500MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WAU240-500T Specifications

Manufacturer WAU240-500T Manufacturer Triad Magnetics Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series WAU240 Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24VAC Current - Output (Max) 500mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals CULus			
Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series WAU240 Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120 VAC Voltage - Output 24 VAC Current - Output (Max) 500mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Manufacturer Part Number	WAU240-500T	
AC AC Wall Adapters Package Series WAU240 Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24VAC Current - Output (Max) Fower (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals	Manufacturer	Triad Magnetics	
Package - Series WAU240 Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24VAC Current - Output (Max) 500mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Category	Power Supplies - External/Internal (Off-Board)	
SeriesWAU240Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output24VACCurrent - Output (Max)500mAPower (Watts)12WNo Load Power Consumption210mW (Max)ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-10°C ~ 50°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)ApprovalscULus		AC AC Wall Adapters	
Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output24VACCurrent - Output (Max)500mAPower (Watts)12WNo Load Power Consumption210mW (Max)ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature-10°C ~ 50°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)ApprovalscULus	Package	-	
Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24VAC Current - Output (Max) 500mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Series	WAU240	
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24VAC Current - Output (Max) 500mA Power (Watts) 12W No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) cULus	Region Utilized	North America	
Voltage - Input Voltage - Output 24VAC Current - Output (Max) 500mA Power (Watts) 12W No Load Power Consumption Applications ITE (Commercial) Efficiency Level VI Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals	Form	Wall Mount (Class II)	
Voltage - Output (Max) 500mA Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Input Type	Fixed Blade	
Current - Output (Max) Power (Watts) 12W No Load Power Consumption Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) cULus	Voltage - Input	120VAC	
Power (Watts) 12W No Load Power Consumption 210mW (Max) Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Voltage - Output	24VAC	
No Load Power Consumption Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Current - Output (Max)	500mA	
Applications ITE (Commercial) Efficiency Level VI Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Power (Watts)	12W	
Efficiency Level VI Operating Temperature $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $1.89^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 3.15^{\circ}\text{H} (48.0\text{mm} \times 60.0\text{mm} \times 80.0\text{mm})$ Approvals cULus	No Load Power Consumption	210mW (Max)	
Operating Temperature -10°C ~ 50°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Applications	ITE (Commercial)	
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) cULus	Efficiency	Level VI	
Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cULus	Operating Temperature	-10°C ~ 50°C	
Approvals cULus	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm	
	Size / Dimension	1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)	
Report errors?	Approvals	cULus	
Report offolis.			Report errors?

WAU240-500T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WAU240-500T Payment Methods





















WAU240-500T Shipping Methods













If you have any question about WAU240-500T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com