

WDU12-300 Information

Heisener.com

Part Number WDU12-300
Manufacturer Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MNT ADAPTER 12V 300MA

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WDU12-300 Specifications

Manufacturer Part Number WDU12-300 Manufacturer Triad Magnetics Category Power Supplies - External/Internal (Off-Board)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series WDU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120V AC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Manufacturer Part Number	WDU12-300
Package - Series WDU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Manufacturer	Triad Magnetics
Package - Series WDU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesWDURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input 120 VACVoltage - Output $12V$ Current - Output (Max) 300 mAPower (Watts)-No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature -10° C ~ 40° COutput ConnectorBarrel Plug, 2.1 mm I.D. x 5.5 mm O.D. x 11.0 mmSize / Dimension 2.76° L x 1.97° W x 1.61° H (70.0 mm x 50.0 mm x 41.0 mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension x 41.0mm)	Series	WDU
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 120VAC 12V 12V 12V 10 Current - Output (Max) 10 C ~ 40 ° C	Form	Wall Mount
Voltage - Output (Max) 300mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 300mA	Voltage - Input	120VAC
Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Voltage - Output	12V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature -10° C ~ 40° COutput ConnectorBarrel Plug, $2.1 \text{ mm I.D. x 5.5 mm O.D. x 11.0 mm}$ Size / Dimension 2.76° L x 1.97° W x 1.61° H ($70.0 \text{ mm x 50.0 mm x 41.0 mm}$)	Current - Output (Max)	300mA
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Power (Watts)	-
Applications ITE (Commercial) Efficiency - Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $2.76^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.61^{\circ}\text{H} (70.0\text{mm} \times 50.0\text{mm} \times 41.0\text{mm})$	No Load Power Consumption	-
Efficiency -	Polarization	Positive Center
Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76° L x 1.97° W x 1.61° H (70.0mm x 50.0mm x 41.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Efficiency	-
Size / Dimension 2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)	Operating Temperature	-10°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm
Report errors?	Size / Dimension	2.76" L x 1.97" W x 1.61" H (70.0mm x 50.0mm x 41.0mm)
•		Report errors?

WDU12-300 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WDU12-300 Payment Methods





















WDU12-300 Shipping Methods













If you have any question about WDU12-300, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com