

WDU18-250 Information

Heisener.com

Part Number WDU18-250
Manufacturer Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MNT ADPTR 18V 250MA

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WDU18-250 Specifications

Manufacturer Part Number WDU18-250 Manufacturer Triad Magnetics Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series WDU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 250mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension Pagenct arrange		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series WDU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 250mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Manufacturer Part Number	WDU18-250
Package-SeriesWDURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output18VCurrent - Output (Max)250mAPower (Watts)-No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Manufacturer	Triad Magnetics
Package - Series WDU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 250mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesWDURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output18VCurrent - Output (Max)250mAPower (Watts)-No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)		AC DC Desktop, Wall Adapters
Region Utilized Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension North America North America North America North America Wall Mount 120VAC 18V 250mA 250mA Power (Watts) - Output (Connector) Positive Center - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 250mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Series	WDU
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 250mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 18V Current - Output (Max) 250mA Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 120VAC 18V 120VAC 18V 250mA Power (Watts) - C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Form	Wall Mount
Voltage - Output (Max) 250mA Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Voltage - Input	120VAC
Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Voltage - Output	18V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Current - Output (Max)	250mA
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Power (Watts)	-
Applications ITE (Commercial) Efficiency - Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	No Load Power Consumption	-
Efficiency - $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $2.52^{\circ}\text{L} \times 2.01^{\circ}\text{W} \times 1.61^{\circ}\text{H} (64.0\text{mm} \times 51.0\text{mm} \times 41.0\text{mm})$	Polarization	Positive Center
Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Efficiency	-
Size / Dimension 2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)	Operating Temperature	-10°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm
Papart arrors?	Size / Dimension	2.52" L x 2.01" W x 1.61" H (64.0mm x 51.0mm x 41.0mm)
Report errors:		Report errors?

WDU18-250 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WDU18-250 Payment Methods



















WDU18-250 Shipping Methods













If you have any question about WDU18-250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com