

WDU9-2300

WDU9-2300 Information

Heisener.com	Part Number Manufacturer Category Description Package	WDU9-2300 Triad Magnetics Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC WALL MOUNT ADAPTER 9V 2.3A - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



WDU9-2300 Specifications

Manufacturer Part NumberWDU9-2300ManufacturerTriad MagneticsCategoryPower Supplies - External/Internal (Off-Board)Ac DC Desktop, Wall AdaptersPackage-SeriesWDURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output9VCurrent - Output (Max)-Power (Watts)-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarel Plug, 2.1nm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 65.0mm)		
CategoryPower Supplies - External/Internal (Off-Board) AC DC Desktop, Wall AdaptersPackage-SeriesWDURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output (Max)9VCurrent - Output (Max)-Power (Watts)-PolarizationPositive CenterApplicationsITE (commercial)Efficiency-Operating Temperature-0°C Output ConnectorBarel Plug, 2.1nm I.D. x 5.5mm O.D. x 11.0mmSiz / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 65.0mm x 55.0mm)	Manufacturer Part Number	WDU9-2300
AC DC Desktop, Wall AdaptersPackage-SeriesWDURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output9VCurrent - Output (Max)2.3APower (Watts)-No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Manufacturer	Triad Magnetics
Package-SeriesWDURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output9VCurrent - Output (Max)-Power (Watts)-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBartel Plug 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.55" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesWDURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output9VCurrent - Output (Max)2.3APower (Watts)-No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dinension3.35" L x 2.68" W x 2.17" H (85.0mm x 55.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 2.3A Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.35" L x 2.68" W x 2.17" H (85.0mm x 65.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 9V Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Operating Temperature -0°C ~ 40°C Output Connector Bartel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.35" L x 2.68" W x 2.17" H (85.0mm x 65.0mm)	Series	WDU
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 2.3A Power (Watts) - No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Region Utilized	North America
Voltage - Input120VACVoltage - Output9VCurrent - Output (Max)2.3APower (Watts)-No Load Power Consumption-PolarizationPositive CenterApplicationsTE (Commercial)Efficiency-Operating Temperature-0°C Output ConnectorBartel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 55.0mm)	Form	Wall Mount
Voltage - Output9VCurrent - Output (Max)2.3APower (Watts)-No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 55.0mm)	Input Type	Fixed Blade
Current - Output (Max) 2.3A Power (Watts) - No Load Power Consumption - Polarization Positive Center Polarizations ITE (Commercial) Applications - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.35" L x 2.68" W x 2.17" H (85.0mm x 55.0mm)	Voltage - Input	120VAC
Power (Watts)-Power (Watts)-No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Voltage - Output	9V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 55.0mm)	Current - Output (Max)	2.3A
PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Power (Watts)	-
ApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 55.0mm)	No Load Power Consumption	-
Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Polarization	Positive Center
Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Efficiency	-
Size / Dimension 3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)	Operating Temperature	$-10^{\circ}\mathrm{C} \sim 40^{\circ}\mathrm{C}$
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm
Report errors?	Size / Dimension	3.35" L x 2.68" W x 2.17" H (85.0mm x 68.0mm x 55.0mm)
		Report errors?

WDU9-2300 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

WIRE
transfer PayPai Image: Construction of the state Image: Construction of the state WDU9-2300 Shipping Methods Image: Construction of the state Image: Cons

If you have any question about WDU9-2300, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com