



WFH160L1R0KE Information



For Reference Only

Part Number WFH160L1R0KE

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1 OHM 10% 160W

Package Radial, Rectangular Case

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WFH160L1R0KE Specifications

Manufacturer Part Number WFH160L1R0KE Manufacturer Ohmite Category Resistors Package Radial, Rectangular Case Series WFH Resistance 1 Ohms Tolerance ±10% Power (Watts) 160W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -		
Category Resistors Package Radial, Rectangular Case Series WFH Resistance 1 Ohms Tolerance ±10% Power (Watts) 160W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Manufacturer Part Number	WFH160L1R0KE
Chassis Mount Resistors Package Radial, Rectangular Case WFH Resistance 1 Ohms Tolerance ±10% Power (Watts) 160W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension Feight - Seated (Max) Lead Style Solder Lugs Package / Case Failure Rate Chassis Mount Resistors Radial, Rectangular Case Radial, Rectangular Case Failure Rate Cobersis Sup / Dimensiors Chassis Mount Resistors WFH Aluminum Wirewound	Manufacturer	Ohmite
PackageRadial, Rectangular CaseSeriesWFHResistance1 OhmsTolerance±10%Power (Watts)160WCompositionWirewoundTemperature Coefficient-Operating Temperature-40°C ~ 220°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension5.512" L x 2.008" W (140.00mm x 51.00mm)Height - Seated (Max)0.496" (12.60mm)Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Category	Resistors
Series WFH Resistance 1 Ohms Tolerance ±10% Power (Watts) 160W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -		Chassis Mount Resistors
Resistance1 OhmsTolerance±10%Power (Watts)160WCompositionWirewoundTemperature Coefficient-Operating Temperature-40°C ~ 220°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension5.512" L x 2.008" W (140.00mm x 51.00mm)Height - Seated (Max)0.496" (12.60mm)Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Package	Radial, Rectangular Case
Tolerance ±10% Power (Watts) 160W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Series	WFH
Power (Watts) Composition Wirewound Temperature Coefficient Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) Lead Style Package / Case Radial, Rectangular Case Failure Rate -	Resistance	1 Ohms
Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Tolerance	±10%
Temperature Coefficient Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Power (Watts)	160W
Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate	Temperature Coefficient	-
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Operating Temperature	-40°C ~ 220°C
Mounting Feature Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Features	-
Size / Dimension 5.512" L x 2.008" W (140.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 0.496" (12.60mm) Solder Lugs Radial, Rectangular Case -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Size / Dimension	5.512" L x 2.008" W (140.00mm x 51.00mm)
Package / Case Radial, Rectangular Case Failure Rate -	Height - Seated (Max)	0.496" (12.60mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

WFH160L1R0KE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WFH160L1R0KE Payment Methods



















WFH160L1R0KE Shipping Methods













If you have any question about WFH160L1R0KE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com