



### WFH230L100JE Information

www.helsener.com

For Reference Only

Part Number WFH230L100JE

Manufacturer Ohmite
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 100 OHM 5% 230W

Package Radial, Rectangular Case

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# WFH230L100JE Specifications

Manufacturer Part Number       WFH230L100JE         Manufacturer       Ohmite         Category       Resistors         Package       Radial, Rectangular Case         Series       WFH         Resistance       100 Ohms         Tolerance       ±5%         Power (Watts)       230W         Composition       Wirewound         Temperature Coefficient       -         Operating Temperature       -40°C ~ 220°C         Features       -         Coating, Housing Type       Aluminum         Mounting Feature       Flanges         Size / Dimension       8.268" L x 2.008" W (210.00mm x 51.00mm)         Height - Seated (Max)       0.496" (12.60mm)         Lead Style       Solder Lugs         Package / Case       Radial, Rectangular Case         Failure Rate       -		
CategoryResistorsPackageRadial, Rectangular CaseSeriesWFHResistance100 OhmsTolerance±5%Power (Watts)230WCompositionWirewoundTemperature Coefficient-Operating Temperature-40°C ~ 220°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension8.268" L x 2.008" W (210.00mm x 51.00mm)Height - Seated (Max)0.496" (12.60mm)Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Manufacturer Part Number	WFH230L100JE
Chassis Mount Resistors           Package         Radial, Rectangular Case           Series         WFH           Resistance         100 Ohms           Tolerance         ±5%           Power (Watts)         230W           Composition         Wirewound           Temperature Coefficient         -           Operating Temperature         -40°C ~ 220°C           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         8.268" L x 2.008" W (210.00mm x 51.00mm)           Height - Seated (Max)         0.496" (12.60mm)           Lead Style         Solder Lugs           Package / Case         Radial, Rectangular Case           Failure Rate         -	Manufacturer	Ohmite
PackageRadial, Rectangular CaseSeriesWFHResistance100 OhmsTolerance±5%Power (Watts)230WCompositionWirewoundTemperature Coefficient-Operating Temperature-40°C ~ 220°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension8.268" L x 2.008" W (210.00mm x 51.00mm)Height - Seated (Max)0.496" (12.60mm)Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Category	Resistors
Series         WFH           Resistance         100 Ohms           Tolerance         ±5%           Power (Watts)         230W           Composition         Wirewound           Temperature Coefficient         -           Operating Temperature         -40°C ~ 220°C           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         8.268" L x 2.008" W (210.00mm x 51.00mm)           Height - Seated (Max)         0.496" (12.60mm)           Lead Style         Solder Lugs           Package / Case         Radial, Rectangular Case           Failure Rate         -		Chassis Mount Resistors
Resistance100 OhmsTolerance±5%Power (Watts)230WCompositionWirewoundTemperature Coefficient-Operating Temperature-40°C ~ 220°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension8.268" L x 2.008" W (210.00mm x 51.00mm)Height - Seated (Max)0.496" (12.60mm)Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Package	Radial, Rectangular Case
Tolerance ±5%  Power (Watts) 230W  Composition Wirewound  Temperature Coefficient - Operating Temperature  -40°C ~ 220°C  Features - Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm)  Height - Seated (Max) 0.496" (12.60mm)  Lead Style Solder Lugs  Package / Case Radial, Rectangular Case  Failure Rate -	Series	WFH
Power (Watts)  Composition  Wirewound  Temperature Coefficient  Operating Temperature  -40°C ~ 220°C  Features  - Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  8.268" L x 2.008" W (210.00mm x 51.00mm)  Height - Seated (Max)  Lead Style  Package / Case  Radial, Rectangular Case  Failure Rate  -	Resistance	100 Ohms
Composition Wirewound  Temperature Coefficient - Operating Temperature -40°C ~ 220°C  Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm)  Height - Seated (Max) 0.496" (12.60mm)  Lead Style Solder Lugs  Package / Case Radial, Rectangular Case  Failure Rate -	Tolerance	±5%
Temperature Coefficient  Operating Temperature  -40°C ~ 220°C  Features  - Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  8.268" L x 2.008" W (210.00mm x 51.00mm)  Height - Seated (Max)  0.496" (12.60mm)  Lead Style  Solder Lugs  Package / Case  Radial, Rectangular Case  Failure Rate  -	Power (Watts)	230W
Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm)  Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Temperature Coefficient	-
Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  8.268" L x 2.008" W (210.00mm x 51.00mm)  Height - Seated (Max)  0.496" (12.60mm)  Lead Style  Solder Lugs  Package / Case  Radial, Rectangular Case  Failure Rate  -	Operating Temperature	-40°C ~ 220°C
Mounting Feature  Size / Dimension  8.268" L x 2.008" W (210.00mm x 51.00mm)  Height - Seated (Max)  0.496" (12.60mm)  Lead Style  Package / Case  Radial, Rectangular Case  Failure Rate  -	Features	-
Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm)  Height - Seated (Max) 0.496" (12.60mm)  Lead Style Solder Lugs  Package / Case Radial, Rectangular Case  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Failure Rate  0.496" (12.60mm)  Solder Lugs  Radial, Rectangular Case  -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Size / Dimension	8.268" L x 2.008" W (210.00mm x 51.00mm)
Package / Case Radial, Rectangular Case Failure Rate -	Height - Seated (Max)	0.496" (12.60mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

#### WFH230L100JE Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## WFH230L100JE Payment Methods





















## WFH230L100JE Shipping Methods













If you have any question about WFH230L100JE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com