



WFH330L250JE Information

www.heisener.com

For Reference Only

Part Number WFH330L250JE

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 250 OHM 5% 330W

Package Radial, Rectangular Case

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WFH330L250JE Specifications

Manufacturer Part Number WFH330L250JE Manufacturer Ohmite Category Resistors Chassis Mount Resistors Package Radial, Rectangular Case Series WFH Resistance 250 Ohms Tolerance ±5% Power (Watts) 330W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate - Report errors?		
CategoryResistorsPackageRadial, Rectangular CaseSeriesWFHResistance250 OhmsTolerance±5%Power (Watts)330WCompositionWirewoundTemperature Coefficient-Operating Temperature-40°C ~ 220°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension11.024" L x 2.008" W (280.00mm x 51.00mm)Height - Seated (Max)0.496" (12.60mm)Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Manufacturer Part Number	WFH330L250JE
Chassis Mount Resistors Package Radial, Rectangular Case Series WFH Resistance 250 Ohms Tolerance ±5% Power (Watts) 330W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Manufacturer	Ohmite
PackageRadial, Rectangular CaseSeriesWFHResistance250 OhmsTolerance±5%Power (Watts)330WCompositionWirewoundTemperature Coefficient-Operating Temperature-40°C ~ 220°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension11.024" L x 2.008" W (280.00mm x 51.00mm)Height - Seated (Max)0.496" (12.60mm)Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Category	Resistors
Series WFH Resistance 250 Ohms Tolerance ±5% Power (Watts) 330W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -		Chassis Mount Resistors
Resistance250 OhmsTolerance±5%Power (Watts)330WCompositionWirewoundTemperature Coefficient-Operating Temperature-40°C ~ 220°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension11.024" L x 2.008" W (280.00mm x 51.00mm)Height - Seated (Max)0.496" (12.60mm)Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Package	Radial, Rectangular Case
Tolerance ±5% Power (Watts) 330W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Series	WFH
Power (Watts) Composition Wirewound Temperature Coefficient Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) Lead Style Package / Case Radial, Rectangular Case Failure Rate -	Resistance	250 Ohms
Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Package / Case Radial, Rectangular Case Failure Rate -	Power (Watts)	330W
Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Package / Case Radial, Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Temperature Coefficient	-
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Package / Case Radial, Rectangular Case Failure Rate -	Operating Temperature	-40°C ~ 220°C
Mounting Feature Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Package / Case Radial, Rectangular Case Failure Rate -	Features	-
Size / Dimension 11.024" L x 2.008" W (280.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 0.496" (12.60mm) Solder Lugs Radial, Rectangular Case -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Size / Dimension	11.024" L x 2.008" W (280.00mm x 51.00mm)
Package / Case Radial, Rectangular Case Failure Rate -	Height - Seated (Max)	0.496" (12.60mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

WFH330L250JE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WFH330L250JE Payment Methods

































If you have any question about WFH330L250JE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com