

WKO392MCPQG0KR

WKO392MCPQG0KR Information

www.heisener.com	WKO392MCPQG0KR Vishay BC Components Capacitors Ceramic Capacitors CAP CER 3900PF 440VAC Y5U RADIAL Radial, Disc For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



WKO392MCPQG0KR Specifications

Manufacturer Part Number WKC332MCPQG0KR Manufacturer Vishay BC Components Category Capacitors Category Caramic Capacitors Package Radial, Disc Series WKO Capacitance 3900pF Tolerance ±20% Voltage - Rated 440VAC Temperature Coefficient Y5U (E) Operating Temperature - Applications X1, Y2 Applications Safety Failure Rate - Mounting Type Inrough Hole Size / Dimension 0,630° Dia (16.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.295° (7.50mm)		
CategoryCaracitorsCaranic CapacitorsPackageRadial, DiscSeriesWKOCapacitance3900pFTolerance±20%Voltage - Rated440VACTomperature CoefficientY5U (E)Operating Temperature-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingSuffy (7.50mm)Lead StyleStraight	Manufacturer Part Number	WKO392MCPQG0KR
Indext Ceramic CapacitorsPackageRadial, DiscSeriesWKOCapacitance3900pFTolerance±20%Voltage - Rated440VACTemperature CoefficientY5U (E)Operating Temperature-Peatures-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeSafetyPackage / CaseRadia, DiscSize / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.295° (7.50mm)Lead StyleStraight	Manufacturer	Vishay BC Components
PackageRadial, DiscSeriesWKOCapacitance3900pFTolerance±20%Voltage - Rated440VACTemperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeNongh HoleSack / CaseRadia, DiscSize / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingSurger, T.Somm,Lead StyleStraight	Category	Capacitors
SeriesWKOCapacitance3900pFTolerance±20%Voltage - Rated440VACTemperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeThrough HoleSize / Dimension0.630° Dia (16.00mm)Height - Seated (Max)0.748" (19.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleStraight		Ceramic Capacitors
Capacitance3900pFTolerance±20%Voltage - Rated440VACTemperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-RatingsX1 Y2ApplicationsSafetyFailure Rate-Mounting TypeMough HoleSize / Dimension0130° Dia (16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing029° (7.50mm)Lead StyleStraight	Package	Radial, Disc
Tolerance±20%Voltage - Rated440VACTemperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.295° (7.50mm)Lead StyleStraight	Series	WKO
Voltage - Rated440VACTemperature CoefficientV5U (E)Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Thickness (Max)0.748° (19.00mm)Lead Spacing0.295° (7.50mm)Lead StyleStraight	Capacitance	3900pF
Temperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeThrough HoleSackage / CaseRadial, DiscSize / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.295° (7.50mm)Lead StyleStraight	Tolerance	±20%
Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630" Dia (16.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleStringhtString Maximum Cast (Max)StringhtString Ma	Voltage - Rated	440VAC
Features-Features-RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.748" (19.00mm)Thickness (Max).Lead Spacing0.295" (7.50mm)Lead StyleStraight	Temperature Coefficient	Y5U (E)
RatingsX1, Y2ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.748" (19.00mm)Thickness (Max)0.295" (7.50mm)Lead SpacingStraight	Operating Temperature	-40°C ~ 125°C
ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.748" (19.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleStraight - Seated (Max)	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.748" (19.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleStraight	Ratings	X1, Y2
Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.748" (19.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleStraight - Seated (Max)	Applications	Safety
Package / CaseRadial, DiscSize / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.748" (19.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.748" (19.00mm) Thickness (Max) - Lead Spacing 0.295" (7.50mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max)0.748" (19.00mm)Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleStraight	Package / Case	Radial, Disc
Thickness (Max)-Lead Spacing0.295" (7.50mm)Lead StyleStraight	Size / Dimension	0.630" Dia (16.00mm)
Lead Spacing0.295" (7.50mm)Lead StyleStraight	Height - Seated (Max)	0.748" (19.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.295" (7.50mm)
Report errors?	Lead Style	Straight
		Report errors?

WKO392MCPQG0KR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

WKO392MCPQG0KR Payment Methods



If you have any question about WKO392MCPQG0KR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com